

GREASES



MARINE GREASE

- Boat trailer chassis lubrication
- Boat trailer wheel bearing lubrication
- Boat overdrive/outboards
- Boat steering linkage
- Industrial equipment
- Multi-Purpose
- Fresh water and salt water rust and corrosion protection
- Environmentally safe
- GC-LB




HEAVY DUTY MINING & CONSTRUCTION GREASE

- Automotive chassis lubrication
- Industrial equipment
- Construction equipment
- Multi-purpose
- Heavy duty equipment
- Agricultural equipment
- Logging equipment
- Mining equipment



RED "N" TACKY® GREASE

- Automotive chassis lubrication
- Automotive wheel bearing lubrication
- Industrial equipment
- Construction equipment
- Heavy duty equipment
- Multi-Purpose
- GC-LB



X-TRA HEAVY DUTY GREASE

- Automotive chassis lubrication
- Automotive wheel bearing lubrication
- Industrial equipment
- Electrical contacts
- Multi-Purpose
- Heavy duty equipment
- CVJ
- GC-LB



WHITE LITHIUM GREASE

- Automotive chassis lubrication
- Industrial equipment
- Household
- Doors/Hinges
- Garage Doors

LUCAS OIL®

LucasOil.com

61030

AVAILABLE PART NUMBERS

MARINE GREASE

10320-30 30PK - 14 OZ	10321 35 LB PAIL
10322 120 LB KEG	10660 400 LB DRUM
10682 3 - 3 OZ	11148 12 CASE - 1 LB TUB

HEAVY DUTY MINING & CONSTRUCTION GREASE

10881-30 30 PK - 14 OZ	10922 120 LB KEG
----------------------------------	----------------------------

WHITE LITHIUM GREASE

10533 8 OZ	10535 35 LB PAIL
----------------------	----------------------------

RED "N" TACKY® GREASE

10676 2.5 OZ	10005 14 OZ
10574 1 LB	10027 35 LB
10028 120 LB	10029 400 LB

X-TRA HEAVY DUTY GREASE

10301 14 OZ	10330 16 OZ
-----------------------	-----------------------

GREASES

PROPERTY / APPLICATION	X-TRA HEAVY DUTY	RED "N" TACKY®	WHITE LITHIUM	MINING & CONSTRUCTION	MARINE
NLGI Grade	2	2	2	2	2
NLGI Certified	GC-LB	GC-LB	No	Yes	GC-LB
Thickener Type	Polyurea	Calcium Sulfonate	Li-12 Hydroxystearate	Lithium Complex	Calcium Sulfonate
Tacky/Adhesive	No	Yes	No	Yes	Yes
Color	Green	Red	White	Dark Gray/Black	Blue
Appearance	Buttery	Buttery	Buttery	Buttery	Buttery
Worked Pen. at 77°F, 1/10 mm	265-295	265-295	265-295	265-290	265-295
Dropping Point °F	>560	>540	360	>500	>540
Rust Protection	✓	✓	✓	✓	✓
Salt Water Corrosion Protection	Fair	Good	Poor	Good	Excellent
Operating Temperature	-20 to 400°F	-20 to 350°F	-10 to 275°F	-4 to 400°F	-20 to 350°F
Low Temperature Torque @ -40°F	Pass	Pass	Pass	Pass	Pass
Automotive Chassis Lubrication	✓	✓	✓	✓	✓
Automotive Wheel Bearing Lubrication	✓	✓	No	No	✓
Industrial Equipment	✓	✓	✓	✓	✓
Electrical Contacts	✓	No	No	No	No
Heavy Duty/Construction Equipment	✓	✓	No	✓	✓
Constant Velocity Joints (CVJ)	✓	No	No	✓	No
Boat Trailer Wheel Bearings	No	✓	No	No	✓
Boat Trailer Chassis Lubrication	✓	✓	No	No	✓
Boat Outdrive	No	✓	No	No	✓
Automotive and Boat Steering Linkage	✓	✓	✓	✓	✓
Centralized Delivery Systems	✓	No	✓	No	No
Extreme Pressure Properties	✓	✓	No	✓	✓
Timken OK Load, Lbs	70	60	<40	70+	65
Industrial Plain bearings	✓	✓	✓	✓	✓
Anti-Friction Bearings above 5000 rpms	✓	No	✓	No	No
Household Use	✓	✓	✓	No	✓
Shock Load Protection	✓	✓	No	✓	✓
Multi-Purpose Grease	✓	✓	No	No	✓
Water Resistance	Excellent	Excellent	Good	Good	Excellent
Environmentally Safe	Fair	Good	Fair	Fair	Excellent

LUCAS OIL®

LucasOil.com