



LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET

SEMI-SYNTHETIC SAE 10W-40 ATV / UTV OIL



Lucas Semi-Synthetic SAE 10W-40 High Performance ATV/UTV is a specially formulated ATV/UTV oil for enhanced engine cleanliness and wear protection. This formulation delivers top-tier resistance against the formation of gums, sludges, and varnish, delivering extended oil life and outstanding engine cleanliness. Our semi-synthetic formulation is polymer modified to deliver outstanding low temperature fluidity, especially important for cold climates, while maintaining maximum film thickness at high operating temperatures and speeds. Our formulation provides outstanding protection for either air-cooled or water-cooled engines.

Lucas Semi-Synthetic SAE 10W-40 High Performance ATV/UTV Oil is formulated to provide powerful lubrication to avoid high engine temperatures and low oil pressure resulting in increased performance and quiet operation. Our premium ATV/UTV oil provides outstanding wear protection for your engine and helps improve fuel economy and oil drain interval. Choose Lucas Oil to keep your equipment in premium condition, season after season.

PART NUMBER AND SIZE:

10720 – 1 Quart

FEATURES AND BENEFITS:

- Specialty formulation for enhanced engine cleanliness.
- Extreme wear protection for vital engine and transmission components.
- Resists oxidation and formation of sludge and varnish
- Shear-stable polymers for high temperature film thickness and long oil life.
-

SPECIFICATIONS, APPROVALS AND RECOMMENDATIONS:

Meets or exceeds:

API SN/SM/SL/SJ, JASO MA / MA-2

MAIN APPLICATIONS:

Formulated to meet the performance requirements of all ATV's and UTV's that specify a Semi-Synthetic SAE 10W-40 motor oil.



LUCAS OIL PRODUCTS, INC. PRODUCT DATA SHEET

TYPICAL PHYSICAL CHARACTERISTICS:

PROPERTIES	ASTM	TYPICAL
API Gravity	D4052	32.0
Specific Gravity @ 60°F	D4052	0.8654
Density @ 60°F, Lbs/US Gal	D4052	7.206
Viscosity @ 40°C cSt	D445	81
Viscosity @ 100°C cSt	D445	14
Viscosity Index	D2270	180
Color		Amber
Flash Point, COC °F	D92	422

These characteristics are typical of current production. However, slight variations in these characteristics may occur.

LINKS AND ADDITIONAL INFORMATION:

For additional product or health and safety information, including product Safety Data Sheets, visit [LucasOil.com](https://www.LucasOil.com)