

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 6/18/2025 Revision date: 10/23/2025 Supersedes: 6/24/2025 Version: 3.0

SECTION 1 Identification**1.1. Product identifier**

Product form : Mixture
Product name : SAE 50 Plus Racing Engine Oil
Part Number : 10107

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricating oil

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924
International: 1-813-248-0585
(collect calls accepted)

SECTION 2 Hazard Identification**2.1. Classification of the substance or mixture****GHS US classification**

| | | |
|---|------|--------------------------------------|
| Serious eye damage/eye irritation, Category 2 | H319 | Causes serious eye irritation. |
| Skin sensitization, Category 1 | H317 | May cause an allergic skin reaction. |

Full text of H statements : see section 16

2.2. Label elements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P302+P352 - If on skin: Wash with plenty of water.

SAE 50 Plus Racing Engine Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|---|---------------------|----------|---|
| Distillates (petroleum), hydrotreated heavy paraffinic | CAS-No.: 64742-54-7 | 45 - 70* | Asp. Tox. 1, H304 |
| Paraffin oils (petroleum), catalytic dewaxed heavy | CAS-No.: 64742-70-7 | 10 - 30* | Asp. Tox. 1, H304 |
| Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts | CAS-No.: 68457-79-4 | 1 - 5* | Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 3, H402 Aquatic Chronic 3, H412 |
| Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo) | CAS-No.: 72030-25-2 | 0.1 - 1* | Skin Irrit. 2, H315 Skin Sens. 1, H317 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

| | |
|---|---|
| First-aid measures general | : If you feel unwell, seek medical advice. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor/physician if you feel unwell. |
| First-aid measures after skin contact | : Take off contaminated clothing and wash it before reuse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center/doctor/physician if you feel unwell. |
| Personal protection for first-aid responders. | : First aid workers will be equipped with suitable personal protective equipment. |

SAE 50 Plus Racing Engine Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

4.2. Most important symptoms/effects, acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : Not expected to present a significant inhalation hazard under anticipated conditions of normal use. |
| Symptoms/effects after skin contact | : May cause an allergic skin reaction. Redness. Skin rash/inflammation. Itching. May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. Blurred vision. redness, itching, tears. Eye irritation. |
| Symptoms/effects after ingestion | : Not expected to present a significant ingestion hazard under anticipated conditions of normal use. |

4.3. Indication of immediate medical attention and special treatment needed, if necessary

| | |
|-----------------------------------|--------------------------|
| Other medical advice or treatment | : Treat symptomatically. |
|-----------------------------------|--------------------------|

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Specific hazards arising from the chemical

| | |
|--|--|
| Fire hazard | : In case of fire and/or explosion do not breathe fumes. |
| Explosion hazard | : No direct explosion hazard. |
| Hazardous decomposition products in case of fire | : Carbon monoxide. Carbon dioxide. |

5.3. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|---|
| Firefighting instructions | : Evacuate area. Eliminate all ignition sources if safe to do so. Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|---|
| General measures | : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage. |
|------------------|---|

For non-emergency personnel

| | |
|----------------------|---|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. |

For emergency responders

| | |
|---------------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel. Stop leak if safe to do so. |
| Environmental precautions | : Avoid release to the environment. |

6.2. Methods and materials for containment and cleaning up

| | |
|-----------------|---|
| For containment | : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. |
|-----------------|---|

SAE 50 Plus Racing Engine Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| | |
|-------------------------|---|
| Methods for cleaning up | : Take up liquid spill into absorbent material. Take up liquid spill into absorbent material. Move containers from spill area. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|--|
| Precautions for safe handling | : Ensure good ventilation of the work station. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Do not breathe vapors. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. |
| Hygiene measures | : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. |
| Additional hazards when processed | : Not expected to present a significant hazard under anticipated conditions of normal use. |

7.2. Conditions for safe storage, including incompatibilities

| | |
|---------------------|---|
| Technical measures | : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container tightly closed. Containers which are opened should be properly resealed and kept upright to prevent leakage. |
| Storage conditions | : Keep cool. Protect from sunlight. |
| Packaging materials | : Store always product in container of same material as original container. |

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

| | |
|----------------------------------|--|
| Appropriate engineering controls | : Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station. |
| Environmental exposure controls | : Avoid release to the environment. |

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

| |
|-----------------------------------|
| Hand protection: |
| Protective gloves |
| Eye protection: |
| Safety glasses |
| Skin and body protection: |
| Wear suitable protective clothing |

SAE 50 Plus Racing Engine Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

| | |
|---|-----------------------------------|
| Physical state | : Liquid |
| Color | : No data available |
| Odor | : No data available |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : > 200 °C |
| Flammability (solid, gas) | : Not applicable. |
| Vapor pressure | : No data available |
| Relative vapor density at 20°C | : No data available |
| Relative density | : 0.89 |
| Density | : 7.429 lb/gal |
| Solubility | : No data available |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : 166 mm ² /s @ 40 ° C |
| Explosion limits | : No data available |
| Particle characteristics | : Particle size : Not Applicable |

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

SAE 50 Plus Racing Engine Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

| | |
|--------------------|---|
| LD50 oral rat | > 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |
| LD50 dermal rabbit | > 2000 mg/kg Source: ECHA |

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

| | |
|--------------------|-----------------------------|
| LD50 dermal rabbit | > 5000 mg/kg Source: IUCLID |
|--------------------|-----------------------------|

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4)

| | |
|--------------------|--|
| LD50 oral rat | 3600 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 20000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal) |
| ATE US (oral) | 3600 mg/kg body weight |

Skin corrosion/irritation : Not classified

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4)

| | |
|----|-------------------------------------|
| pH | No data available in the literature |
|----|-------------------------------------|

Serious eye damage/irritation : Causes serious eye irritation.

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4)

| | |
|----|-------------------------------------|
| pH | No data available in the literature |
|----|-------------------------------------|

Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

| | |
|---|--|
| LOAEL (oral,rat,90 days) | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| NOAEC (inhalation,rat,dust/mist/fume,90 days) | > 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study) |

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

| | |
|--------------------------|--|
| LOAEL (oral,rat,90 days) | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
|--------------------------|--|

SAE 50 Plus Racing Engine Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|---|
| NOAEC (inhalation, rat, dust/mist/fume, 90 days) | > 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study) |

Aspiration hazard : Not classified

| SAE 50 Plus Racing Engine Oil | |
|-------------------------------|---------------------------------|
| Viscosity, kinematic | 166 mm ² /s @ 40 ° C |

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|-----------------------|
| Viscosity, kinematic | 18 mm ² /s |
| Hydrocarbon | Yes |
| Aliphatic, alicyclic or aromatic hydrocarbon | Yes |

| Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4) | |
|--|---|
| Viscosity, kinematic | 264.8 mm ² /s (40 °C, ASTM D445: Capillary viscometer) |

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction. Redness. Skin rash/inflammation. Itching. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye irritation. Blurred vision. redness, itching, tears. Eye irritation.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|----------------------------|
| LC50 - Fish [1] | > 5000 mg/l |
| EC50 - Crustacea [1] | > 1000 mg/l Source: IUCLID |
| EC50 96h - Algae [1] | > 1000 mg/l Source: IUCLID |

| Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4) | |
|--|---|
| LC50 - Fish [1] | 46 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Cyprinodon variegatus, Semi-static system, Marine water, Experimental value, GLP) |

12.2. Persistence and degradability

| SAE 50 Plus Racing Engine Oil | |
|-------------------------------|---|
| Persistence and degradability | Biodegradability in water: no data available. |

| Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7) | |
|---|------------------------|
| Persistence and degradability | Not rapidly degradable |

SAE 50 Plus Racing Engine Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|------------------------|
| Persistence and degradability | Not rapidly degradable |

| Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo) (72030-25-2) | |
|--|------------------------|
| Persistence and degradability | Not rapidly degradable |

| Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4) | |
|--|-------------------------------------|
| Persistence and degradability | Not readily biodegradable in water. |

12.3. Bioaccumulative potential

| SAE 50 Plus Racing Engine Oil | |
|-------------------------------|---|
| Bioaccumulative potential | No data available concerning bioaccumulation. |

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 3.9 – 6 Source: IUCLID |

| Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4) | |
|--|---|
| Partition coefficient n-octanol/water (Log Pow) | 0.69 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 21.8 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

12.4. Mobility in soil

| SAE 50 Plus Racing Engine Oil | |
|-------------------------------|--------------------------------------|
| Ecology - soil | No additional information available. |

| Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4) | |
|--|---|
| Surface tension | 61.1 mN/m (21 °C, 1.25 g/l, EU Method A.5: Surface tension) |
| Ecology - soil | No (test)data on mobility of the substance available. |

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

| DOT | TDG | IMDG | IATA |
|-----------------------------|-----|------|------|
| 14.1. UN number | | | |
| Not regulated for transport | | | |

SAE 50 Plus Racing Engine Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| DOT | TDG | IMDG | IATA |
|---|---------------|---------------|---------------|
| 14.2. Proper Shipping Name | | | |
| Not regulated | Not regulated | Not regulated | Not regulated |
| 14.3. Transport hazard class(es) | | | |
| Not regulated | Not regulated | Not regulated | Not regulated |
| 14.4. Packing group | | | |
| Not regulated | Not regulated | Not regulated | Not regulated |
| 14.5. Environmental hazards | | | |
| Not regulated | Not regulated | Not regulated | Not regulated |
| No supplementary information available | | | |

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

Not regulated

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

SAE 50 Plus Racing Engine Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-kappaS,kappaS']dioxodi-mu-thioxodi-, (Mo-Mo) (72030-25-2)

Listed on the Canadian DSL (Domestic Substances List)

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (68457-79-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 10/23/2025
Issue date : 6/18/2025
Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.

Full text of hazard classes and H-statements

| | |
|------|---|
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H402 | Harmful to aquatic life |
| H412 | Harmful to aquatic life with long lasting effects |

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.