

SECTION 1 Identification**1.1. Product identifier**

Product form : Mixture
Product name : Synthetic SAE 5W-40 Motor Oil
Part Number : 10189

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricating oil

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

SECTION 2 Hazard Identification**2.1. Classification of the substance or mixture****GHS US classification**

Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.

Full text of H statements : see section 16

2.2. Label elements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H317 - May cause an allergic skin reaction
H361 - Suspected of damaging fertility or the unborn child

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

Synthetic SAE 5W-40 Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

P302+P352 - If on skin: Wash with plenty of water.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	65 - 85*	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	10 - 30*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Benzenamine, ar-nonyl-N-(nonylphenyl)-	CAS-No.: 36878-20-3	0.5 - 1.5*	Repr. 2, H361 Aquatic Chronic 4, H413
Calcium long chain alkaryl sulfonate	CAS-No.: 722503-69-7	0.1 - 1*	Skin Sens. 1, H317

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders. : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : May cause an allergic skin reaction.
Symptoms/effects after eye contact : None under normal conditions.

Synthetic SAE 5W-40 Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

Synthetic SAE 5W-40 Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
----------------	----------

Synthetic SAE 5W-40 Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Color	: Mixture contains one or more component(s) which have the following color(s): Colourless White to grey
Odor	: There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odor: Characteristic odour Almost odourless
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.846
Density	: 7.063 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 89.87 mm ² /s @ 40 ° C
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Synthetic SAE 5W-40 Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	5000 mg/kg
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	5000 mg/kg body weight

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified

Synthetic SAE 5W-40 Motor Oil	
Viscosity, kinematic	89.87 mm ² /s @ 40 ° C

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Viscosity, kinematic	12 mm ² /s
Hydrocarbon	Yes

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	18 mm ² /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Symptoms/effects after inhalation : None under normal conditions.

Synthetic SAE 5W-40 Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
LC50 - Fish [1]	> 0.0013 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

Synthetic SAE 5W-40 Motor Oil	
Persistence and degradability	Not rapidly degradable
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Persistence and degradability	Not rapidly degradable
Calcium long chain alkaryl sulfonate (722503-69-7)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

Synthetic SAE 5W-40 Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow) 3.9 – 6 Source: IUCLID

12.4. Mobility in soil

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Mobility in soil 35900000 Source: EPISUITE

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

Not regulated

Synthetic SAE 5W-40 Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Listed on the Canadian DSL (Domestic Substances List)

Calcium long chain alkaryl sulfonate (722503-69-7)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Revision date : 5/5/2026

Issue date : 6/7/2025

Synthetic SAE 5W-40 Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements	
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H361	Suspected of damaging fertility or the unborn child
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.