

**SECTION 1 Identification****1.1. Product identifier**

Product form : Mixture  
Product name : AW ISO 46 Hydraulic Oil  
Part Number : 10406

**1.2. Other means of identification**

No additional information available

**1.3. Recommended use of the chemical and restrictions on use**

Use of the substance/mixture : Lubricating oil

**1.4. Supplier's details**

Lucas  
47112  
T 800-342-2512  
[sds@lucasoil.com](mailto:sds@lucasoil.com) - [www.LucasOil.com](http://www.LucasOil.com)

**1.5. Emergency phone number**

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week  
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924  
International: 1-813-248-0585  
(collect calls accepted)

**SECTION 2 Hazard Identification****2.1. Classification of the substance or mixture****GHS US classification**

Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Hazardous to the aquatic environment — Acute Hazard, Category 3	H402	Harmful to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

**2.2. Label elements****GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H361 - Suspected of damaging fertility or the unborn child  
H402 - Harmful to aquatic life  
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.  
P308+P313 - If exposed or concerned: Get medical advice/attention.

# AW ISO 46 Hydraulic Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	80-100*	Asp. Tox. 1, H304
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	CAS-No.: 68411-46-1	0.1 - 1*	Repr. 2, H361 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4 First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

# AW ISO 46 Hydraulic Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

##### For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Ventilate spillage area.

##### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.  
Environmental precautions : Avoid release to the environment.

#### 6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.  
Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

# AW ISO 46 Hydraulic Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### 7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up.
Packaging materials	: Store always product in container of same material as original container.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
[In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following color(s): Light yellow Colourless Colourless to light yellow Yellow to brown Yellow
Odor	: There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odor: Mild odour Irritating/pungent odour Aromatic odour Pleasant odour Petroleum-like odour Sweet odour Ammonia odour Odourless Asphyxiating odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available

# AW ISO 46 Hydraulic Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Flash point	: > 200 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.855
Density	: 7.143 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 44.08 mm <sup>2</sup> /s
Explosion limits	: No data available
Particle characteristics	: Particle size : Not Applicable

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

#### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

LD50 oral rat	> 5000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
---------------	---

# AW ISO 46 Hydraulic Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
LD50 dermal rat	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Skin)

Skin corrosion/irritation : Not classified

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
pH	5.1 – 6.2 (1 %, 20 - 25 °C)

Serious eye damage/irritation : Not classified

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
pH	5.1 – 6.2 (1 %, 20 - 25 °C)

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
NOAEL (animal/male, F1)	54 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
NOAEL (oral,rat,90 days)	25 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard : Not classified

<b>AW ISO 46 Hydraulic Oil</b>	
Viscosity, kinematic	44.08 mm <sup>2</sup> /s

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Viscosity, kinematic	18 mm <sup>2</sup> /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
Viscosity, kinematic	353 mm <sup>2</sup> /s (40 °C, OECD 114: Viscosity of Liquids)

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : None under normal conditions.

# AW ISO 46 Hydraulic Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### SECTION 12 Ecological information

#### 12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Harmful to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	51 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)

#### 12.2. Persistence and degradability

<b>AW ISO 46 Hydraulic Oil</b>	
Persistence and degradability	Not rapidly degradable

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Persistence and degradability	Not rapidly degradable

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
Persistence and degradability	Not readily biodegradable in water.

#### 12.3. Bioaccumulative potential

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
BCF - Fish [1]	1730 (42 day(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across, GLP)
Partition coefficient n-octanol/water (Log Pow)	6.66 (Experimental value, OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method, 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

#### 12.4. Mobility in soil

<b>Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)</b>	
Mobility in soil	60460 Source: EPISUITE

# AW ISO 46 Hydraulic Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.754 – 8.947 (log Koc, SRC PCKOCWIN v2.0, QSAR)
--	--

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

### 12.5. Other adverse effects

Ozone : Not classified  
Fluorinated greenhouse gases : No

## SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.

## SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
Not regulated for transport			
<b>14.2. Proper Shipping Name</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

**DOT**  
Not regulated

**TDG**  
Not regulated

**IMDG**  
Not regulated

**IATA**  
Not regulated

# AW ISO 46 Hydraulic Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### SECTION 15 Regulatory information

#### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### 15.2. International regulations

##### CANADA

##### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

##### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

No additional information available

##### National regulations


##### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### 15.3. State regulations

 **WARNING:** This product can expose you to Cumene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 10/7/2025

Issue date : 7/8/2025

#### Full text of hazard classes and H-statements

H304	May be fatal if swallowed and enters airways
H361	Suspected of damaging fertility or the unborn child
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.