

**Safety Data Sheet**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)  
Issue date: 7/24/2025 Revision date: 12/2/2025 Supersedes: 7/24/2025 Version: 2.0

**SECTION 1 Identification****1.1. Product identifier**

Product form : Mixture  
Product name : SxS UTV Multi-Purpose Gearcase & Differential Fluid  
Part Number : 18052

**1.2. Other means of identification**

No additional information available

**1.3. Recommended use of the chemical and restrictions on use**

Use of the substance/mixture : Lubricating oil

**1.4. Supplier's details**

Lucas Oil Products, Inc.  
3199 Harrison Way NW  
Corydon, IN 47112  
USA  
T 800-342-2512  
[sds@lucasoil.com](mailto:sds@lucasoil.com) - [www.LucasOil.com](http://www.LucasOil.com)

**1.5. Emergency phone number**

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week  
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924  
International: 1-813-248-0585  
(collect calls accepted)

**SECTION 2 Hazard Identification****2.1. Classification of the substance or mixture****GHS US classification**

Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411	Toxic to aquatic life with long lasting effects.

Full text of H statements : see section 16

**2.2. Label elements****GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

H361 - Suspected of damaging fertility or the unborn child  
H400 - Very toxic to aquatic life  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P391 - Collect spillage.  
P405 - Store locked up.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	30 - 60*	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic	CAS-No.: 64742-55-8	5 - 10*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
1-Decene, homopolymer, hydrogenated	CAS-No.: 68037-01-4	5 - 10*	Asp. Tox. 1, H304
1-Dodecene, polymer with 1-decene, hydrogenated	CAS-No.: 151006-60-9	5 - 10*	Asp. Tox. 1, H304
1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated	CAS-No.: 68649-12-7	3 - 7*	Asp. Tox. 1, H304
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated	CAS-No.: 134758-95-5	1 - 5*	Aquatic Chronic 4, H413
Benzenamine, N-phenyl-, reaction products with alkenes	CAS-No.: Undisclosed	1 - 5*	Repr. 2, H361 Aquatic Chronic 3, H412
tert-Butylphenyl diphenyl phosphate	CAS-No.: 56803-37-3	1 - 5*	Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Amines, alkyl phosphates	CAS-No.: Undisclosed	0.5 - 1.5*	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### SECTION 4 First aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

#### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

##### For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area.

##### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment.

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### 6.2. Methods and materials for containment and cleaning up

For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

### 7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up.
Packaging materials	: Always store product in container of same material as original container.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

#### 1-Decene, homopolymer, hydrogenated (68037-01-4)

#### USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Inhalable fraction)
-----------------	--

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following color(s): Colourless Colourless to light yellow Colourless or white
Odor	: There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odor: Mild odour Characteristic odour Odourless Sweet odour Phenol odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.867
Density	: 7.238 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 126.1 mm <sup>2</sup> /s @ 40 ° C
Explosion limits	: No data available
Particle characteristics	: Particle size : Not Applicable

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	5000 mg/kg
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	5000 mg/kg body weight

#### 1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)

LD50 oral rat	> 5000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 3000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapors)	0.9 mg/l Source: ECHA
ATE US (vapors)	0.9 mg/l/4h

#### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID

#### 1-Decene, homopolymer, hydrogenated (68037-01-4)

LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
-----------------	---

Skin corrosion/irritation : Not classified

#### 1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)

pH	3.9 Source: ECHA
----	------------------

Serious eye damage/irritation : Not classified

#### 1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)

pH	3.9 Source: ECHA
----	------------------

Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
STOT-single exposure : Not classified

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

STOT-repeated exposure : Not classified

<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified

<b>SxS UTV Multi-Purpose Gearcase &amp; Differential Fluid</b>	
Viscosity, kinematic	126.1 mm <sup>2</sup> /s @ 40 ° C

<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b>	
Viscosity, kinematic	12 mm <sup>2</sup> /s
Hydrocarbon	Yes

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : None under normal conditions.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b>	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

<b>1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)</b>	
LC50 - Fish [1]	> 1000 mg/l Source: e-ChemPortal;HPVIS
EC50 96h - Algae [1]	> 1000 mg/l Source: e-ChemPortal;HPVIS

<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

<b>tert-Butylphenyl diphenyl phosphate (56803-37-3)</b>	
LC50 - Fish [1]	0.037 mg/l Source: Ecological Structure Activity Relationships
EC50 96h - Algae [1]	0.035 mg/l Source: Ecological Structure Activity Relationships

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### 12.2. Persistence and degradability

#### SxS UTV Multi-Purpose Gearcase & Differential Fluid

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### 1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### 1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated (134758-95-5)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Benzenamine, N-phenyl-, reaction products with alkenes (Undisclosed)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Amines, alkyl phosphates (Undisclosed)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Persistence and degradability	Biodegradability in water: no data available.
-------------------------------	---

#### tert-Butylphenyl diphenyl phosphate (56803-37-3)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

### 12.3. Bioaccumulative potential

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

#### 1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)

Partition coefficient n-octanol/water (Log Pow)	7.64 Source: e-ChemPortal;HPVIS
---	---------------------------------

#### 1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)

Partition coefficient n-octanol/water (Log Pow)	5
---	---

#### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

#### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

#### tert-Butylphenyl diphenyl phosphate (56803-37-3)

Partition coefficient n-octanol/water (Log Pow)	5.12 Source: Hazardous Substances Data Bank
---	---

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### 12.4. Mobility in soil

#### 1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)

Mobility in soil 192200000 Source: EPISUITE

#### tert-Butylphenyl diphenyl phosphate (56803-37-3)

Mobility in soil 22650 Source: EPI Suite

### 12.5. Other adverse effects





Ozone : Not classified  
 Fluorinated greenhouse gases : No

## SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.  
 Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
 Sewage disposal recommendations : Disposal must be done according to official regulations.  
 Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
 Additional information : Do not re-use empty containers.

## SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
UN3082	UN3082	UN3082	UN3082
<b>14.2. Proper Shipping Name</b>			
Environmentally hazardous substances, liquid, n.o.s. (tert-Butylphenyl diphenyl phosphate )	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (tert-Butylphenyl diphenyl phosphate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (tert-Butylphenyl diphenyl phosphate)	Environmentally hazardous substance, liquid, n.o.s. (tert-Butylphenyl diphenyl phosphate)
<b>14.3. Transport hazard class(es)</b>			
9	9	9	9
			
<b>14.4. Packing group</b>			
III	III	III	III
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			
<b>14.6. Transport in bulk</b>			
Not applicable			

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### 14.7. Special precautions for user

#### DOT

UN-No. (DOT)	: UN3082
DOT Special Provisions (49 CFR 172.102)	: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 173 - An appropriate generic entry may be used for this material. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 155
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No Limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No Limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

#### TDG

UN-No. (TDG) : UN3082

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, may be offered for transport, handled or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport. (2) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Emergency Response Guide (ERG) Number	: 171

### IMDG

Special provision (IMDG)	: 274, 335, 375, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A

### IATA

Special provision (IATA)	: A97, A158, A197, A215
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

ERG code (IATA)

: 9L

### SECTION 15 Regulatory information

#### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Benzenamine, N-phenyl-, reaction products with alkenes	CAS-No. Undisclosed	1 - 5*%
Amines, alkyl phosphates	CAS-No. Undisclosed	0.5 - 1.5*%
1-Decene, homopolymer, hydrogenated	CAS-No. 68037-01-4	5 - 10*%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### 15.2. International regulations

##### CANADA

##### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

##### 1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)

Listed on the Canadian DSL (Domestic Substances List)

##### 1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)

Listed on the Canadian DSL (Domestic Substances List)

##### Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated (134758-95-5)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

##### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Listed on the Canadian DSL (Domestic Substances List)

##### tert-Butylphenyl diphenyl phosphate (56803-37-3)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

No additional information available

##### National regulations

No additional information available

#### 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# SxS UTV Multi-Purpose Gearcase & Differential Fluid

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 12/2/2025

Issue date : 7/24/2025

Full text of hazard classes and H-statements	
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.