

SECTION 1 Identification**1.1. Product identifier**

Product form : Mixture
Product name : Bore Solvent & Ultrasonic Gun Cleaner
Part Number : 10909

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricating oil

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924
International: 1-813-248-0585
(collect calls accepted)

SECTION 2 Hazard Identification**2.1. Classification of the substance or mixture****GHS US classification**

Reproductive toxicity, Category 1	H360	May damage fertility or the unborn child.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410	Very toxic to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements**GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H304 - May be fatal if swallowed and enters airways
H360 - May damage fertility or the unborn child
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P331 - Do NOT induce vomiting.
P391 - Collect spillage.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	80 - 100*	Asp. Tox. 1, H304
Sulfonic acids, petroleum, calcium salts, overbased	CAS-No.: 68783-96-0	1 - 5*	Eye Irrit. 2, H319 Aquatic Chronic 4, H413
Zinc 2-ethylhexanoate	CAS-No.: 136-53-8	0.029 - 0.143	Eye Irrit. 2, H319 Repr. 1, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.
Personal protection for first-aid responders. : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : None under normal conditions.

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung edema.
Chronic symptoms	: May damage fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
----------------	----------

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Color	: Mixture contains one or more component(s) which have the following color(s): Colourless to yellow Yellow Light yellow Pure substance: white Unpurified: yellow to brown Colourless to light yellow White White to light yellow On exposure to light: discolours Light yellow to yellow Colourless On exposure to air: brown
Odor	: There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odor: Aromatic odour Solvent-like odour Mild odour Phenol odour Tar odour Floral odour Fruity odour Irritating/pungent odour Pleasant odour Strong odour Odourless Ammonia odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 221 °F
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.837
Density	: 6.987 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 3 mm²/s @ 40 ° C
Explosion limits	: No data available
Particle characteristics	: Particle size : Not Applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 oral	15000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l Source: IUCLID
ATE US (oral)	15000 mg/kg body weight

Sulfonic acids, petroleum, calcium salts, overbased (68783-96-0)

LD50 oral rat	> 20000 mg/kg Source: International Uniform Chemical Information Database
LD50 dermal rabbit	> 20000 mg/kg Source: International Uniform Chemical Information Database

Zinc 2-ethylhexanoate (136-53-8)

LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value of similar product, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value of similar product, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value of similar product, Inhalation (aerosol), 7 day(s))
LC50 Inhalation - Rat (Dust/Mist)	> 5.7 mg/l Source: ECHA

Skin corrosion/irritation : Not classified

Zinc 2-ethylhexanoate (136-53-8)

pH	No data available in the literature
----	-------------------------------------

Serious eye damage/irritation : Not classified

Zinc 2-ethylhexanoate (136-53-8)

pH	No data available in the literature
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: May damage fertility or the unborn child.

Distillates (petroleum), hydrotreated light (64742-47-8)

NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (oral, rat, 90 days)	750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Zinc 2-ethylhexanoate (136-53-8)	
NOAEL (subchronic, oral, animal/male, 90 days)	180 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: other:
NOAEL (subchronic, oral, animal/female, 90 days)	205 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: other:
Aspiration hazard	: May be fatal if swallowed and enters airways.
Bore Solvent & Ultrasonic Gun Cleaner	
Viscosity, kinematic	3 mm ² /s @ 40 ° C
Zinc 2-ethylhexanoate (136-53-8)	
Viscosity, kinematic	No data available in the literature
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung edema.
Chronic symptoms	: May damage fertility or the unborn child.
SECTION 12 Ecological information	
12.1. Ecotoxicity	
Ecology - general	: Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.
Sulfonic acids, petroleum, calcium salts, overbased (68783-96-0)	
EC50 - Crustacea [1]	> 1000 mg/l Source: International Uniform Chemical Information Database
EC50 96h - Algae [1]	> 1000 mg/l Source: International Uniform Chemical Information Database
Zinc 2-ethylhexanoate (136-53-8)	
LC50 - Fish [1]	100 mg/l Source: ECHA
EC50 - Crustacea [1]	0.15 – 0.53 mg/l (48 h, Ceriodaphnia dubia, Literature study, Zinc ion)
12.2. Persistence and degradability	
Bore Solvent & Ultrasonic Gun Cleaner	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated light (64742-47-8)	
Persistence and degradability	Not rapidly degradable
Sulfonic acids, petroleum, calcium salts, overbased (68783-96-0)	
Persistence and degradability	Not rapidly degradable

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Zinc 2-ethylhexanoate (136-53-8)			
Persistence and degradability	Readily biodegradable in water.		
12.3. Bioaccumulative potential			
Distillates (petroleum), hydrotreated light (64742-47-8)			
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID		
Zinc 2-ethylhexanoate (136-53-8)			
BCF - Other aquatic organisms [1]	38 (28 day(s), <i>Palaemon elegans</i> , Semi-static system, Marine water, Read-across, Fresh weight)		
Partition coefficient n-octanol/water (Log Pow)	> 5.7 (Read-across, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
12.4. Mobility in soil			
Zinc 2-ethylhexanoate (136-53-8)			
Surface tension	63.62 mN/m (20 °C, 90 %)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.2 (log Koc, Calculated value)		
Ecology - soil	Low potential for adsorption in soil.		
12.5. Other adverse effects			
Ozone	: Not classified		
Fluorinated greenhouse gases	: No		
SECTION 13 Disposal considerations			
Regional waste regulation	: Disposal must be done according to official regulations.		
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.		
Sewage disposal recommendations	: Disposal must be done according to official regulations.		
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.		
Additional information	: Do not re-use empty containers.		
SECTION 14 Transport information			
In accordance with DOT / TDG / IMDG / IATA			
DOT	TDG	IMDG	IATA
14.1. UN number			
UN3082	UN3082	3082	3082
14.2. Proper Shipping Name			
Environmentally hazardous substances, liquid, n.o.s. (Zinc 2-ethylhexanoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc 2-ethylhexanoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc 2-ethylhexanoate)	Environmentally hazardous substance, liquid, n.o.s. (Zinc 2-ethylhexanoate)

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT	TDG	IMDG	IATA
14.3. Transport hazard class(es)			
9	9	9	9
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT)

DOT Special Provisions (49 CFR 172.102)

: UN3082

: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

173 - An appropriate generic entry may be used for this material.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s." UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx)

: 155

DOT Packaging Non Bulk (49 CFR 173.xxx)

: 203

DOT Packaging Bulk (49 CFR 173.xxx)

: 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)

: No Limit

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)

: No Limit

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

TDG

UN-No. (TDG)

: UN3082

TDG Special Provisions

: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3).
(2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:
(a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S;
(b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S;
(c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S;
(d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or
(e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.
(3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:
(a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or
(b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, may be offered for transport, handled or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport.
(2) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.

Explosive Limit and Limited Quantity Index

: 5 L

Excepted quantities (TDG)

: E1

Emergency Response Guide (ERG) Number

: 171

IMDG

Special provision (IMDG)

: 274, 335, 375, 969

Limited quantities (IMDG)

: 5 L

Excepted quantities (IMDG)

: E1

Packing instructions (IMDG)

: LP01, P001

Packing provisions (IMDG)

: PP1

IBC packing instructions (IMDG)

: IBC03

Tank instructions (IMDG)

: T4

Tank special provisions (IMDG)

: TP1, TP29

ErMS-No. (Fire)

: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE

ErMS-No. (Spillage)

: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS

Stowage category (IMDG)

: A

IATA

Special provision (IATA)

: A97, A158, A197, A215

PCA Excepted quantities (IATA)

: E1

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

PCA Limited quantities (IATA)	:	Y964
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	964
PCA max net quantity (IATA)	:	450L
CAO packing instructions (IATA)	:	964
CAO max net quantity (IATA)	:	450L
ERG code (IATA)	:	9L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

Sulfonic acids, petroleum, calcium salts, overbased (68783-96-0)

Listed on the Canadian DSL (Domestic Substances List)

Zinc 2-ethylhexanoate (136-53-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Zinc 2-ethylhexanoate (136-53-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations



This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 12/9/2025

Issue date : 9/12/2025

Bore Solvent & Ultrasonic Gun Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Full text of hazard classes and H-statements	
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H360	May damage fertility or the unborn child
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.