

SECTION 1 Identification**1.1. Product identifier**

Product form : Mixture
Product name : Extreme Duty CLP
Part Number : 10908

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricating oil

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924
International: 1-813-248-0585
(collect calls accepted)

SECTION 2 Hazard Identification**2.1. Classification of the substance or mixture****GHS US classification**

Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 1	H360	May damage fertility or the unborn child.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Hazardous to the aquatic environment — Acute Hazard, Category 3	H402	Harmful to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements**GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H304 - May be fatal if swallowed and enters airways
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H360 - May damage fertility or the unborn child

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Precautionary statements (GHS US)

- H402 - Harmful to aquatic life
- H412 - Harmful to aquatic life with long lasting effects
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
- P264 - Wash hands, forearms and face thoroughly after handling.
- P272 - Contaminated work clothing must not be allowed out of the workplace.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
- P301+P310 - If swallowed: Immediately call a poison center or doctor.
- P302+P352 - If on skin: Wash with plenty of water.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 - If exposed or concerned: Get medical advice/attention.
- P321 - Specific treatment (see supplemental first aid instruction on this label).
- P331 - Do NOT induce vomiting.
- P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
- P337+P313 - If eye irritation persists: Get medical advice or attention.
- P362+P364 - Take off contaminated clothing and wash it before reuse.
- P405 - Store locked up.
- P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	60 - 80*	Asp. Tox. 1, H304
Sulfonic acids, petroleum, calcium salts, overbased	CAS-No.: 68783-96-0	7 - 13*	Eye Irrit. 2, H319 Aquatic Chronic 4, H413
Sulfonic acids, petroleum, calcium salts	CAS-No.: 61789-86-4	1 - 5*	Skin Sens. 1B, H317
Sulfonic acids, petroleum, sodium salts	CAS-No.: 68608-26-4	< 100	Skin Irrit. 2, H315 Eye Dam. 1, H318

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung edema.
Chronic symptoms	: May damage fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapors/spray.

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following color(s): Colourless Colourless to yellow Yellow Light yellow Pure substance: white Unpurified: yellow to brown Colourless to light yellow White White to light yellow On exposure to light: discolours Light yellow to yellow On exposure to air: brown
Odor	: There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odor: Aromatic odour Solvent-like odour Mild odour Phenol odour Tar odour Floral odour Fruity odour Irritating/pungent odour Pleasant odour Strong odour Odourless Ammonia odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 221 °F
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.862
Density	: 7.203 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 7.103 mm ² /s @ 40 ° C
Explosion limits	: No data available
Particle characteristics	: Particle size : Not Applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 oral	15000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l Source: IUCLID
ATE US (oral)	15000 mg/kg body weight

Sulfonic acids, petroleum, calcium salts, overbased (68783-96-0)

LD50 oral rat	> 20000 mg/kg Source: International Uniform Chemical Information Database
LD50 dermal rabbit	> 20000 mg/kg Source: International Uniform Chemical Information Database

Sulfonic acids, petroleum, calcium salts (61789-86-4)

LD50 oral rat	> 16000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:
LD50 dermal rat	> 2000 mg/kg Source: International Uniform Chemical Information Database
LD50 dermal rabbit	> 4000 mg/kg body weight Animal: rabbit, Guideline: other:
LC50 Inhalation - Rat	> 1.9 mg/l air Animal: rat, Guideline: EPA OPP 81-3 (Acute inhalation toxicity)

Sulfonic acids, petroleum, sodium salts (68608-26-4)

LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 1.9 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Skin corrosion/irritation : Not classified

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
pH	8

Sulfonic acids, petroleum, sodium salts (68608-26-4)	
pH	10

Serious eye damage/irritation : Causes serious eye irritation.

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
pH	8

Sulfonic acids, petroleum, sodium salts (68608-26-4)	
pH	10

Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : May damage fertility or the unborn child.

Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (oral,rat,90 days)	750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Sulfonic acids, petroleum, sodium salts (68608-26-4)	
NOAEL (oral,rat,90 days)	500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways.

Extreme Duty CLP	
Viscosity, kinematic	7.103 mm²/s @ 40 °C

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Risk of lung edema.
Chronic symptoms : May damage fertility or the unborn child.

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Sulfonic acids, petroleum, calcium salts, overbased (68783-96-0)

EC50 - Crustacea [1]	> 1000 mg/l Source: International Uniform Chemical Information Database
EC50 96h - Algae [1]	> 1000 mg/l Source: International Uniform Chemical Information Database

Sulfonic acids, petroleum, calcium salts (61789-86-4)

EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Sulfonic acids, petroleum, sodium salts (68608-26-4)

LC50 - Fish [1]	0.00000301 mg/l Source: Ecological Structure Activity Relationships
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

Extreme Duty CLP

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Distillates (petroleum), hydrotreated light (64742-47-8)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Sulfonic acids, petroleum, calcium salts, overbased (68783-96-0)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Sulfonic acids, petroleum, calcium salts (61789-86-4)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Sulfonic acids, petroleum, sodium salts (68608-26-4)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated light (64742-47-8)

Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID
---	------------------------

Sulfonic acids, petroleum, sodium salts (68608-26-4)

Partition coefficient n-octanol/water (Log Pow)	15.87 Source: Quantitative Structure Activity Relation
---	--

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

IMDG
Not regulated

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

IATA

Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

Sulfonic acids, petroleum, calcium salts, overbased (68783-96-0)

Listed on the Canadian DSL (Domestic Substances List)

Sulfonic acids, petroleum, calcium salts (61789-86-4)

Listed on the Canadian DSL (Domestic Substances List)

Sulfonic acids, petroleum, sodium salts (68608-26-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Sulfonic acids, petroleum, sodium salts (68608-26-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

 **WARNING:** This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Revision date : 1/12/2026

Issue date : 7/15/2025

Extreme Duty CLP

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements	
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H360	May damage fertility or the unborn child
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.