



SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 4/3/2025 Revision date: 8/15/2025 Supersedes: 5/7/2025 Version: 3.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil
Part Number : 10076

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricating oil
Recommended use : Automotive products
Restrictions on use : No additional information available

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN, 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924
International: 1-813-248-0585
(collect calls accepted)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. Label elements

GHS US labeling

No labeling applicable

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	80 - 100*	Asp. Tox. 1, H304
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	CAS-No.: 68649-42-3	0.5-1.5*	Skin Irrit. 2, H315 Eye Irrit. 2, H319
2,5-Furandione, dihydro-, polybutenyl derivs., reaction products with tetraethylenepentamine	CAS-No.: 68583-75-5	1 - 5*	Aquatic Chronic 4, H413

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Wash skin with plenty of water. Get medical attention if symptoms occur.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide.

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

5.3. Special protective equipment and precautions for fire-fighters

- | | | |
|--------------------------------|---|---|
| Firefighting instructions | : | Evacuate area. Eliminate all ignition sources if safe to do so. Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : | Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | | |
|------------------|---|---|
| General measures | : | Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage. |
|------------------|---|---|

For non-emergency personnel

- | | | |
|----------------------|---|---|
| Protective equipment | : | Wear recommended personal protective equipment. |
| Emergency procedures | : | Ventilate spillage area. |

For emergency responders

- | | | |
|---------------------------|---|---|
| Protective equipment | : | Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : | Evacuate unnecessary personnel. Stop leak if safe to do so. |
| Environmental precautions | : | Avoid release to the environment. |

6.2. Methods and materials for containment and cleaning up

- | | | |
|-------------------------|---|--|
| For containment | : | Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. |
| Methods for cleaning up | : | Take up liquid spill into absorbent material. Move containers from fire area if it can be done without personal risk. Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water. |
| Other information | : | Dispose of materials or solid residues at an authorized site. |

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- | | | |
|-----------------------------------|---|---|
| Precautions for safe handling | : | Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe vapors. Avoid contact with skin and eyes. |
| Hygiene measures | : | Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |
| Additional hazards when processed | : | Not expected to present a significant hazard under anticipated conditions of normal use. |

7.2. Conditions for safe storage, including incompatibilities

- | | | |
|--------------------|---|--|
| Technical measures | : | Keep in a cool, well-ventilated place away from heat. |
| Storage conditions | : | Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep only in original container. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. |

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available).

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
If there is a risk of liquid being splashed : Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
No respiratory protection needed under normal use conditions

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.872
Density	: 7.281 lb/gal
Solubility	: No data available

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 108.3 mm ² /s
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

LD50 oral rat	3195 mg/kg Source: ECHA
LD50 dermal rabbit	> 3160 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 5 mg/l air Animal: rat, Guideline: other:
ATE US (oral)	3195 mg/kg body weight

Skin corrosion/irritation	: Not classified
---------------------------	------------------

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

pH	5.5 – 7.5 Concentration: 1 vol%
----	---------------------------------

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Serious eye damage/irritation : Not classified

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

pH	5.5 – 7.5 Concentration: 1 vol%
----	---------------------------------

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

NOAEL (animal/female, F0/P)	300 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:
-----------------------------	--

NOAEL (animal/female, F1)	1000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:
---------------------------	---

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	--

NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
--	---

Aspiration hazard : Not classified

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Viscosity, kinematic	108.3 mm ² /s
----------------------	--------------------------

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Viscosity, kinematic	18 mm ² /s
----------------------	-----------------------

Hydrocarbon	Yes
-------------	-----

Aliphatic, alicyclic or aromatic hydrocarbon	Yes
--	-----

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Viscosity, kinematic	9 – 15 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'
----------------------	--

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.

Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

12.2. Persistence and degradability

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil	
Persistence and degradability	Biodegradability in water: no data available.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
Persistence and degradability	Not rapidly degradable
2,5-Furandione, dihydro-, polybutenyl derivs., reaction products with tetraethylenepentamine (68583-75-5)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil	
Bioaccumulative potential	No data available concerning bioaccumulation.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
Partition coefficient n-octanol/water (Log Pow)	14.876 Source: ECHA

12.4. Mobility in soil

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil	
Ecology - soil	No additional information available.

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

Not regulated

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

SAE 15W-40 Magnum Long Drain Heavy Duty Motor Oil

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Listed on the Canadian DSL (Domestic Substances List)

2,5-Furandione, dihydro-, polybutenyl derivs., reaction products with tetraethylenepentamine (68583-75-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

 **WARNING:** This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 8/15/2025
Issue date : 4/3/2025
Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.

Full text of hazard classes and H-statements

H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.