

SECTION 1: Identification of the hazardous chemical or mixture and of the supplier or manufacturer**1.1. GHS product identifier**

Product form : Mixture
Product name : SAE 85W-140 Heavy Duty Gear Oil
Part Number : 30042

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricating oil
Recommended use : Automotive products

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924
International: 1-813-248-0585
(collect calls accepted)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GHS MX classification**

Hazardous to the aquatic environment – Acute Hazard Category 3 H402 Harmful to aquatic life.
Full text of H statements : see section 16

2.2. Label elements**GHS MX labelling**

Hazard statements (GHS MX) : H402 - Harmful to aquatic life
Precautionary statements (GHS MX) : P273 - Avoid release to the environment.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

Adverse physicochemical, human health and environmental effects : To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice, Harmful to aquatic life

SAE 85W-140 Heavy Duty Gear Oil

Safety Data Sheet

according to NOM-018-STPS-2015

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS MX classification
Paraffin oils (petroleum), catalytic dewaxed heavy	CAS-No.: 64742-70-7	≥ 20 – < 40	Acute Tox. 5 (Dermal), H313 Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	≥ 10 – < 20	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS-No.: 64742-65-0	≥ 5 – < 10	Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313

SECTION 4: First aid measures

4.1. Description of necessary first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Get medical attention if symptoms occur.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide. Water spray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

SAE 85W-140 Heavy Duty Gear Oil

Safety Data Sheet

according to NOM-018-STPS-2015

5.3. Special protective actions for fire-fighters

Firefighting instructions	: Evacuate area. Eliminate all ignition sources if safe to do so. Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Measures to be taken in case of accidental spillage or accidental leakage

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Move containers from fire area if it can be done without personal risk. Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water.
Other information	: Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe vapors. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep only in original container. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers.
Packaging materials	: Always store product in container of same material as original container.

SAE 85W-140 Heavy Duty Gear Oil

Safety Data Sheet

according to NOM-018-STPS-2015

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available).
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

- Personal protective equipment : Wear recommended personal protective equipment.
- Hand protection : Protective gloves
- Eye protection : If there is a risk of liquid being splashed : Safety glasses
- Skin and body protection : Wear suitable protective clothing
- Respiratory protection : No respiratory protection needed under normal use conditions. In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : No data available
- Odor : No data available
- Odor threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : Not applicable
- Freezing point : No data available
- Boiling point : No data available
- Flash point : > 200 °C
- Flammability (solid, gas) : Not applicable
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Vapor pressure : No data available
- Relative vapor density at 20°C : No data available
- Relative density : 0.893
- Density : 7.455 lb/gal
- Solubility : No data available
- Partition coefficient n-octanol/water (Log Pow) : No data available
- Partition coefficient n-octanol/water (Log Kow) : No data available
- Viscosity, kinematic : 335.2 mm²/s
- Viscosity, dynamic : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available
- Explosion limits : No data available

SAE 85W-140 Heavy Duty Gear Oil

Safety Data Sheet

according to NOM-018-STPS-2015

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
ATE MX (dermal)	2500 mg/kg body weight

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LD50 oral	5000 mg/kg
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
ATE MX (oral)	5000 mg/kg body weight
ATE MX (dermal)	5000 mg/kg body weight

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

SAE 85W-140 Heavy Duty Gear Oil

Safety Data Sheet

according to NOM-018-STPS-2015

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)

LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified

SAE 85W-140 Heavy Duty Gear Oil

Viscosity, kinematic	335.2 mm ² /s
----------------------	--------------------------

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Viscosity, kinematic	18 mm ² /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. Harmful to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

SAE 85W-140 Heavy Duty Gear Oil

Safety Data Sheet

according to NOM-018-STPS-2015

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

12.2. Persistence and degradability

SAE 85W-140 Heavy Duty Gear Oil	
Persistence and degradability	Biodegradability in water: no data available.

Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)	
Persistence and degradability	Not rapidly degradable

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

SAE 85W-140 Heavy Duty Gear Oil	
Bioaccumulative potential	No data available concerning bioaccumulation.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 (Calculated)
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

SAE 85W-140 Heavy Duty Gear Oil	
Ecology - soil	No additional information available.

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.
Regional waste regulation	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SAE 85W-140 Heavy Duty Gear Oil

Safety Data Sheet

according to NOM-018-STPS-2015

SECTION 14: Transport information

In accordance with NOM / UN RTDG / IMDG / IATA

NOM	UN RTDG	IMDG	IATA
14.1. UN number			
Not applicable	Not applicable	Not regulated	Not regulated
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not regulated	Not regulated
14.4. Packing group			
Not applicable	Not applicable	Not regulated	Not regulated
14.5. Environmental hazards			
Not applicable	Not applicable	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

NOM

Not applicable

UN RTDG

Not applicable

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7):

Listed in the INSQ (National Inventory of Chemical Substances)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0):

Listed in the INSQ (National Inventory of Chemical Substances)

International regulations

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7):

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the Canadian DSL (Domestic Substances List)

SAE 85W-140 Heavy Duty Gear Oil

Safety Data Sheet

according to NOM-018-STPS-2015

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7):

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the Canadian DSL (Domestic Substances List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0):

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the Canadian DSL (Domestic Substances List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information including those related to the preparation and updating of safety data sheets

Issue date : 5/1/2025
Revision date : 2/26/2026
Supersedes : 5/16/2025

Full text of hazard classes and H-statements

H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways
H313	May be harmful in contact with skin
H402	Harmful to aquatic life

Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstracts Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association

SAE 85W-140 Heavy Duty Gear Oil

Safety Data Sheet

according to NOM-018-STPS-2015

Abbreviations and acronyms	
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organization for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety & Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.

Safety Data Sheet (SDS), Mexico

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.