

TECHNICAL DATA SHEET



SYNTHETIC SAE 0W-30

PRODUCT # 10179, 10181, 10183

API Service SM/SL/SJ/CF

TEST

ASTM

TYPICAL

API Gravity	D-1298	32.8
Specific Gravity @ 60°F	D-1298	.8621
Density @ 60°F LBS/US Gal	D-1298	7.171
Viscosity @ 40°C cSt	D-445	55
Viscosity @ 100°C cSt	D-445	10.5
VI		186
Flash Point, COC °F	D-92	445
Color		Light Brown
Zinc, Wt. %		.12

Lucas Synthetic SAE 0W-30 Motor Oil is a formulation of high quality synthetic base stocks and an exclusive high performance additive package. It's an ideal on track/off track lubricant that ensures minimum drag for maximum fuel mileage, and easy cold weather starting. The user can expect maximum protection from wear even with extended drain intervals.

The exclusive additive package in Lucas Synthetic SAE 0W-30 insures extra protection and longer oil life in turbo charged engines. The user can expect lower oil temperatures and more miles/kilometers between overhauls.

Designed for use in both gasoline and automotive diesel engines.

Meets or exceeds all manufacturers specifications for SAE 0W-30 and API SL and ILSAC GF3.

Exceeds American and European OEM specifications. Exceeds performance levels of API SM/SL/SJ/CF, ACEA A1-08, B1-08, A5-08, B5-08, VW 500/502/505, Daimler Chrysler 229.1 and BMW Longlife Oil.