



Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 5/13/2025 Revision date: 8/27/2026 Supersedes: 7/17/2026 Version: 3.1

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Fuel Treatment
Part Number : 10090

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Fuel additives
Restrictions on use : No additional information available

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Hazardous to the aquatic environment — Chronic Hazard, Category 4 H413 May cause long lasting harmful effects to aquatic life.
Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard statements (GHS US) : H413 - May cause long lasting harmful effects to aquatic life
Precautionary statements (GHS US) : P273 - Avoid release to the environment.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	80 - 100*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
1-Hexanol, 2-ethyl-	CAS-No.: 104-76-7	3 - 7*	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Solvent naphtha (petroleum), light arom.	CAS-No.: 64742-95-6	1 - 5*	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Polyolefin alkyl phenol alkyl amine (1)	CAS-No.: Undisclosed	1 - 5*	Skin Irrit. 2, H315

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Get medical attention if symptoms occur. Wash skin with plenty of water.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Evacuate area. Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material. Move containers from spill area. Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water.
Other information	: Dispose of materials or solid residues at an authorized site.
For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.	

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Do not breathe vapors. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep only in the original container in a cool, well-ventilated place away from: Direct sunlight, Heat sources. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

1-Hexanol, 2-ethyl- (104-76-7)	
USA - ACGIH® - Threshold Limit Values	
Local name	2-Ethyl-1-hexanol
ACGIH® TLV® TWA	5 ppm
Remark (ACGIH®)	TLV® Basis: URT irr & eye irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024

8.2. Appropriate engineering controls

Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:
Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 232.222 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.864
Density	: 7.213 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 95.15 mm²/s @ 40 ° C
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

Solvent naphtha (petroleum), light arom. (64742-95-6)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	---

LD50 dermal rat	> 2000 mg/kg Source: ECHA
-----------------	---------------------------

LC50 Inhalation - Rat (Vapors)	5.16 mg/l Source: ECHA
--------------------------------	------------------------

ATE US (vapors)	5.16 mg/l/4h
-----------------	--------------

1-Hexanol, 2-ethyl- (104-76-7)

LD50 oral rat	2047 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
---------------	--

LD50 oral	2049 mg/kg
-----------	------------

LD50 dermal rat	> 3000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
-----------------	---

LD50 dermal rabbit	1970 mg/kg Source: NLM, THOMSON
--------------------	---------------------------------

LD50 dermal	3000 mg/kg
-------------	------------

LC50 Inhalation - Rat	0.89 – 5.3 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (mixture of vapour and aerosol), 7 day(s))
-----------------------	--

LC50 Inhalation - Rat (Vapors)	4.9 mg/l/4h
--------------------------------	-------------

ATE US (gases)	4500 ppmV/4h
----------------	--------------

ATE US (vapors)	11 mg/l/4h
-----------------	------------

ATE US (dust, mist)	1.5 mg/l/4h
---------------------	-------------

Skin corrosion/irritation : Not classified

1-Hexanol, 2-ethyl- (104-76-7)

pH	7 (0.1 %)
----	-----------

Serious eye damage/irritation : Not classified

1-Hexanol, 2-ethyl- (104-76-7)

pH	7 (0.1 %)
----	-----------

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

1-Hexanol, 2-ethyl- (104-76-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified

Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

1-Hexanol, 2-ethyl- (104-76-7)	
NOAEL (oral, rat, 90 days)	250 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, gas, 90 days)	120 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard : Not classified

Fuel Treatment	
Viscosity, kinematic	95.15 mm²/s @ 40 ° C

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	18 mm²/s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Solvent naphtha (petroleum), light arom. (64742-95-6)	
Viscosity, kinematic	< 1 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'

1-Hexanol, 2-ethyl- (104-76-7)	
Viscosity, kinematic	No data available in the literature

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.

Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : May cause long lasting harmful effects to aquatic life.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : May cause long lasting harmful effects to aquatic life.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

Solvent naphtha (petroleum), light arom. (64742-95-6)	
LC50 - Fish [1]	9.22 mg/l Source: IUCLID

Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Solvent naphtha (petroleum), light arom. (64742-95-6)	
EC50 - Crustacea [1]	6.14 mg/l Source: IUCLID
EC50 72h - Algae [1]	19 mg/l Source: IUCLID
1-Hexanol, 2-ethyl- (104-76-7)	
LC50 - Fish [1]	17.1 mg/l (EU Method C.1, 96 h, Leuciscus idus, Flow-through system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	39 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
LC50 - Fish [2]	28.2 mg/l Test organisms (species): Pimephales promelas
EC50 72h - Algae [1]	11.5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	16.6 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	16.6 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

Fuel Treatment	
Persistence and degradability	Biodegradability in water: no data available.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
Solvent naphtha (petroleum), light arom. (64742-95-6)	
Persistence and degradability	Not rapidly degradable
Polyolefin alkyl phenol alkyl amine (1) (Undisclosed)	
Persistence and degradability	Not rapidly degradable
1-Hexanol, 2-ethyl- (104-76-7)	
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.

12.3. Bioaccumulative potential

Fuel Treatment	
Bioaccumulative potential	No data available concerning bioaccumulation.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Solvent naphtha (petroleum), light arom. (64742-95-6)	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6
1-Hexanol, 2-ethyl- (104-76-7)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

12.4. Mobility in soil

Fuel Treatment

Ecology - soil	No additional information available.
----------------	--------------------------------------

1-Hexanol, 2-ethyl- (104-76-7)

Surface tension	47 mN/m (20 °C, 0.81 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.5475 – 2.1177 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Transport in bulk

Not applicable

Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

IMDG
Not regulated

IATA
Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:		
Polyolefin alkyl phenol alkyl amine (1)	CAS-No. Undisclosed	1 - 5*%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)
Listed on the Canadian DSL (Domestic Substances List)
Solvent naphtha (petroleum), light arom. (64742-95-6)
Listed on the Canadian DSL (Domestic Substances List)
1-Hexanol, 2-ethyl- (104-76-7)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Solvent naphtha (petroleum), light arom. (64742-95-6)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
1-Hexanol, 2-ethyl- (104-76-7)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Fuel Treatment

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

15.3. State regulations

 **WARNING:** This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Revision date : 8/27/2026

Issue date : 5/13/2025

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.