

**Safety Data Sheet**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)  
Issue date: 8/26/2025 Revision date: 10/28/2025 Supersedes: 8/26/2025 Version: 2.0

**SECTION 1 Identification****1.1. Product identifier**

Product form : Mixture  
Product name : Synthetic SAE 10W-60 European Motor Oil  
Part Number : 10251

**1.2. Other means of identification**

No additional information available

**1.3. Recommended use of the chemical and restrictions on use**

Use of the substance/mixture : Lubricating oil  
Recommended use : Lubricating oil  
Restrictions on use : No additional information available

**1.4. Supplier's details**

Lucas Oil Products, Inc.  
3199 Harrison Way NW  
Corydon, IN 47112  
USA  
T 800-342-2512  
[sds@lucasoil.com](mailto:sds@lucasoil.com) - [www.LucasOil.com](http://www.LucasOil.com)

**1.5. Emergency phone number**

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week  
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924  
International: 1-813-248-0585  
(collect calls accepted)

**SECTION 2 Hazard Identification****2.1. Classification of the substance or mixture****GHS US classification**

Not classified

**2.2. Label elements****GHS US labeling**

No labeling applicable

**2.3. Hazards associated with known or reasonably anticipated uses**

No additional information available

**2.4. Hazards not otherwise classified**

No additional information available

**2.5. Unknown acute toxicity**

No additional information available

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### SECTION 3 Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	65 - 85*	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	10 - 30*	Asp. Tox. 1, H304
Benzenamine, ar-nonyl-N-(nonylphenyl)-	CAS-No.: 36878-20-3	1 - 5*	Aquatic Chronic 4, H413

Full text of hazard classes and H-statements : see section 16

### SECTION 4 First aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Take off contaminated clothing and wash it before reuse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

#### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Redness. Skin rash/inflammation. Itching.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard. In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Evacuate area. Eliminate all ignition sources if safe to do so. Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

#### For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

#### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment.

### 6.2. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material. Move containers from spill area. Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe vapors. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

### 7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Packaging materials : Store always product in container of same material as original container.

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available).

Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment

##### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
If there is a risk of liquid being splashed : Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
No respiratory protection needed under normal use conditions. In case of insufficient ventilation, wear suitable respiratory equipment

##### Personal protective equipment symbol(s):



### SECTION 9 Physical and chemical properties

#### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.855
Density	: 7.145 lb/gal
Solubility	: No data available

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 166.3 mm <sup>2</sup> /s
Explosion limits	: No data available
Particle characteristics	: Particle size : Not Applicable

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	5000 mg/kg
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	5000 mg/kg body weight

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

<b>Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)</b>	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Aspiration hazard	: Not classified
<b>Synthetic SAE 10W-60 European Motor Oil</b>	
Viscosity, kinematic	166.3 mm <sup>2</sup> /s
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b>	
Viscosity, kinematic	12 mm <sup>2</sup> /s
Hydrocarbon	Yes
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Viscosity, kinematic	18 mm <sup>2</sup> /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Redness. Skin rash/inflammation. Itching.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
LC50 - Fish [1]	> 0.0013 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna

### 12.2. Persistence and degradability

Synthetic SAE 10W-60 European Motor Oil	
Persistence and degradability	Biodegradability in water: no data available.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Persistence and degradability	Not rapidly degradable

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

Synthetic SAE 10W-60 European Motor Oil	
Bioaccumulative potential	No data available concerning bioaccumulation.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

### 12.4. Mobility in soil

Synthetic SAE 10W-60 European Motor Oil	
Ecology - soil	No additional information available.

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Mobility in soil	35900000 Source: EPISUITE

### 12.5. Other adverse effects

Ozone : Not classified

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Fluorinated greenhouse gases : No

### SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.

### SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
Not regulated for transport			
<b>14.2. Proper Shipping Name</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

#### DOT

Not regulated

#### TDG

Not regulated

#### IMDG

Not regulated

#### IATA

Not regulated

### SECTION 15 Regulatory information

#### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 15.2. International regulations

#### CANADA

##### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

##### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

##### Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

##### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 10/28/2025  
Issue date : 8/26/2025  
Data sources : Supplier's safety documents.  
Training advice : Training staff on good practice.

#### Full text of hazard classes and H-statements

H304	May be fatal if swallowed and enters airways
H413	May cause long lasting harmful effects to aquatic life

#### Abbreviations and acronyms

ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Abbreviations and acronyms	
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organization for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety & Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)

# Synthetic SAE 10W-60 European Motor Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Abbreviations and acronyms	
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.