

**Safety Data Sheet**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)  
Issue date: 4/14/2025 Revision date: 12/2/2025 Supersedes: 7/9/2025 Version: 3.0

**SECTION 1 Identification****1.1. Product identifier**

Product form : Mixture  
Product name : Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40  
Part Number : 10662

**1.2. Other means of identification**

No additional information available

**1.3. Recommended use of the chemical and restrictions on use**

Use of the substance/mixture : Lubricating oil  
Recommended use : Lubricating oil  
Restrictions on use : No additional information available

**1.4. Supplier's details**

Lucas Oil Products, Inc.  
3199 Harrison Way NW  
Corydon, IN 47112  
USA  
T 800-342-2512  
[sds@lucasoil.com](mailto:sds@lucasoil.com) - [www.LucasOil.com](http://www.LucasOil.com)

**1.5. Emergency phone number**

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week  
Within USA, Canada, Puerto Rico and US Virgin Islands: 1-800-255-3924  
International: 1-813-248-0585  
(collect calls accepted)

**SECTION 2 Hazard Identification****2.1. Classification of the substance or mixture****GHS US classification**

Serious eye damage/eye irritation, Category 2 H319 Causes serious eye irritation.  
Full text of H statements : see section 16

**2.2. Label elements****GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning  
Hazard statements (GHS US) : H319 - Causes serious eye irritation  
Precautionary statements (GHS US) : P264 - Wash hands thoroughly after handling.  
P280 - Wear protective gloves, protective clothing, eye and face protection.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 - If eye irritation persists: Get medical advice, Get medical attention.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	80 - 100*	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	7 - 13*	Asp. Tox. 1, H304
Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate)	CAS-No.: 2215-35-2	0.5 - 1.5*	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4 First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water and soap. Take off contaminated clothing. Get medical attention if symptoms occur. Wash skin with plenty of water.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: High concentration of vapors may induce: headache, dizziness, drowsiness, nausea and vomiting.
Symptoms/effects after skin contact	: Redness. Itching.
Symptoms/effects after eye contact	: Causes serious eye irritation. Blurred vision. redness, itching, tears. Eye irritation.

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Ingestion may cause nausea and vomiting. Abdominal pain. Risk of lung edema.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard. In case of fire and/or explosion do not breathe fumes.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate area. Eliminate all ignition sources if safe to do so. Exercise caution when fighting any chemical fire. Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

#### For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Ventilate spillage area. Avoid breathing vapors. Avoid contact with skin and eyes.

#### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.  
Environmental precautions : Avoid release to the environment.

### 6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.  
Methods for cleaning up : Take up liquid spill into absorbent material. Move containers from fire area if it can be done without personal risk. Take up liquid spill into absorbent material. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water.  
Other information : Dispose of materials or solid residues at an authorized site.

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Do not breathe vapors. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

#### 7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep only in original container. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store locked up. Do not store in unlabelled containers.
Incompatible materials	: Direct sunlight.
Packaging materials	: Always store product in container of same material as original container.

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

#### 8.3. Individual protection measures, such as personal protective equipment

##### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

##### Personal protective equipment symbol(s):



# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### SECTION 9 Physical and chemical properties

#### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following color(s): Colourless Pure substance: colourless Unpurified: light yellow Pure substance: white Unpurified: yellow to brown White to grey
Odor	: There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odor: Petroleum-like odour Sweet odour Aromatic odour Tar odour Characteristic odour Almost odourless
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.857
Density	: 7.16 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 101.7 mm <sup>2</sup> /s @ 40 ° C
Explosion limits	: No data available
Particle characteristics	: Particle size : Not Applicable

#### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

### SECTION 10 Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

Oxidizing agent.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### SECTION 11 Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	5000 mg/kg
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	5000 mg/kg body weight

#### Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate) (2215-35-2)

LD50 oral rat	2230 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 25000 mg/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
ATE US (oral)	2230 mg/kg body weight

Skin corrosion/irritation : Not classified

#### Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate) (2215-35-2)

pH	No data available in the literature
----	-------------------------------------

Serious eye damage/irritation : Causes serious eye irritation.

#### Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate) (2215-35-2)

pH	No data available in the literature
----	-------------------------------------

Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

<b>Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate) (2215-35-2)</b>	
NOAEL (oral,rat,90 days)	160 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Aspiration hazard	: Not classified
<b>Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40</b>	
Viscosity, kinematic	101.7 mm <sup>2</sup> /s @ 40 ° C
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Viscosity, kinematic	18 mm <sup>2</sup> /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b>	
Viscosity, kinematic	12 mm <sup>2</sup> /s
Hydrocarbon	Yes
<b>Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate) (2215-35-2)</b>	
Viscosity, kinematic	270.4 mm <sup>2</sup> /s (40 °C, ASTM D445: Capillary viscometer)
Symptoms/effects after inhalation	: High concentration of vapors may induce: headache, dizziness, drowsiness, nausea and vomiting.
Symptoms/effects after skin contact	: Redness. Itching.
Symptoms/effects after eye contact	: Causes serious eye irritation. Blurred vision. redness, itching, tears. Eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Ingestion may cause nausea and vomiting. Abdominal pain. Risk of lung edema.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b>	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

### 12.2. Persistence and degradability

<b>Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40</b>	
Persistence and degradability	Biodegradability in water: no data available.

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Persistence and degradability	Not rapidly degradable
Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate) (2215-35-2)	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40	
Bioaccumulative potential	No data available concerning bioaccumulation.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate) (2215-35-2)	
Partition coefficient n-octanol/water (Log Pow)	2.21 (Practical experience/observation, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40	
Ecology - soil	No additional information available.
Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate) (2215-35-2)	
Surface tension	59.8 mN/m (22 °C, 0.12 %, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Other adverse effects

Ozone : Not classified  
Fluorinated greenhouse gases : No

## SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.

## SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
Not regulated for transport			
<b>14.2. Proper Shipping Name</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

#### DOT

Not regulated

#### TDG

Not regulated

#### IMDG

Not regulated

#### IATA

Not regulated

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 15.2. International regulations

#### CANADA

##### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

### Zinc bis(O,O-bis(1,3-dimethylbutyl) dithiophosphate) (2215-35-2)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### 15.3. State regulations



#### WARNING:

This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date	: 12/2/2025
Issue date	: 4/14/2025
Data sources	: Supplier's safety documents.
Training advice	: Training staff on good practice.

#### Full text of hazard classes and H-statements

H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects

#### Abbreviations and acronyms

ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Abbreviations and acronyms	
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organization for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety & Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

# Extreme Duty Outboard Engine Oil Synthetic SAE 10W-40

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

---

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.