

**SECTION 1 Identification****1.1. Product identifier**

Product form : Mixture  
Product name : Synthetic Blend Marine 2-Cycle Oil  
Part Number : 10860

**1.2. Other means of identification**

No additional information available

**1.3. Recommended use of the chemical and restrictions on use**

Use of the substance/mixture : lubricants  
Recommended use : lubricants

**1.4. Supplier's details**

Lucas Oil Products, Inc.  
3199 Harrison Way NW  
Corydon, IN 47112  
USA  
T 800-342-2512  
[sds@lucasoil.com](mailto:sds@lucasoil.com) - [www.LucasOil.com](http://www.LucasOil.com)

**1.5. Emergency phone number**

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

**SECTION 2 Hazard Identification****2.1. Classification of the substance or mixture****GHS US classification**

Hazardous to the aquatic environment — Chronic Hazard, Category 4 H413 May cause long lasting harmful effects to aquatic life.  
Full text of H statements : see section 16

**2.2. Label elements****GHS US labeling**

Hazard statements (GHS US) : H413 - May cause long lasting harmful effects to aquatic life  
Precautionary statements (GHS US) : P273 - Avoid release to the environment.  
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

**2.3. Hazards associated with known or reasonably anticipated uses**

No additional information available

**2.4. Hazards not otherwise classified**

No additional information available

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### 2.5. Unknown acute toxicity

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	45 - 70*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	15 - 40*	Asp. Tox. 1, H304
White mineral oil (petroleum)	CAS-No.: 8042-47-5	0.5 - 1.5*	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic	CAS-No.: 64742-56-9	5 - 10	Asp. Tox. 1, H304

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4 First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general	: If medical advice is needed, have product container or label at hand. Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Immediately call a poison center or doctor/physician. Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause shortness of breath, tightness of the chest, a sore throat and cough.
Symptoms/effects after skin contact	: Causes skin irritation. Redness. Itching.
Symptoms/effects after eye contact	: Causes serious eye irritation. Blurred vision. redness, itching, tears.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Ingestion may cause nausea and vomiting. Abdominal pain.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard. In case of fire and/or explosion do not breathe fumes.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon monoxide. Carbon dioxide.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate area. Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

##### For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Ventilate spillage area.

##### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.  
Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.  
Methods for cleaning up : Take up liquid spill into absorbent material. Move containers from spill area. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water.  
Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wear personal protective equipment. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Do not breathe vapors.

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

### 7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep only in the original container in a cool, well-ventilated place away from: Direct sunlight, Heat sources. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Packaging materials	: Always store product in container of same material as original container.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

#### White mineral oil (petroleum) (8042-47-5)

#### USA - ACGIH® - Threshold Limit Values

ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Inhalable fraction)
-----------------	--

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: No data available

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.858
Density	: 7.167 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 40.13 mm <sup>2</sup> /s @ 40 ° C
Explosion limits	: No data available
Particle characteristics	: No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 oral	15000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
LC50 Inhalation - Rat (Dust/Mist)	> 5.2 mg/l Source: IUCLID
ATE US (oral)	15000 mg/kg body weight
<b>White mineral oil (petroleum) (8042-47-5)</b>	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol), 14 day(s))
<b>Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)</b>	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: EHCA
Skin corrosion/irritation	: Not classified
<b>White mineral oil (petroleum) (8042-47-5)</b>	
pH	Not applicable (non-soluble in water)
Serious eye damage/irritation	: Not classified
<b>White mineral oil (petroleum) (8042-47-5)</b>	
pH	Not applicable (non-soluble in water)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
NOAEL (oral,rat,90 days)	750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
<b>White mineral oil (petroleum) (8042-47-5)</b>	
NOAEL (oral, rat, 90 days)	≥ 1200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
<b>Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified

<b>Synthetic Blend Marine 2-Cycle Oil</b>	
Viscosity, kinematic	40.13 mm <sup>2</sup> /s @ 40 ° C
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Viscosity, kinematic	18 mm <sup>2</sup> /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
<b>White mineral oil (petroleum) (8042-47-5)</b>	
Viscosity, kinematic	3 – 20.5 mm <sup>2</sup> /s (40 °C, ISO 3104: Determination of kinematic viscosity and calculation of dynamic viscosity, Niet experimenteel bepaald; afgeleid van de indeling)

Symptoms/effects after inhalation : May cause drowsiness or dizziness. May cause shortness of breath, tightness of the chest, a sore throat and cough.

Symptoms/effects after skin contact : Causes skin irritation. Redness. Itching.

Symptoms/effects after eye contact : Causes serious eye irritation. Blurred vision. redness, itching, tears.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Ingestion may cause nausea and vomiting. Abdominal pain.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general : May cause long lasting harmful effects to aquatic life.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : May cause long lasting harmful effects to aquatic life.

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### 12.2. Persistence and degradability

Synthetic Blend Marine 2-Cycle Oil	
Persistence and degradability	Biodegradability in water: no data available.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated light (64742-47-8)	
Persistence and degradability	Not rapidly degradable
White mineral oil (petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water.
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

Synthetic Blend Marine 2-Cycle Oil	
Bioaccumulative potential	No data available concerning bioaccumulation.
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Distillates (petroleum), hydrotreated light (64742-47-8)	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID
White mineral oil (petroleum) (8042-47-5)	
BCF - Other aquatic organisms [1]	1216 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5.2 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

### 12.4. Mobility in soil

Synthetic Blend Marine 2-Cycle Oil	
Ecology - soil	No additional information available.
White mineral oil (petroleum) (8042-47-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.6 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

### 12.5. Other adverse effects

Ozone : Not classified  
Fluorinated greenhouse gases : No

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

### SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

### SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
Not regulated for transport			
<b>14.2. Proper Shipping Name</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

#### 14.6. Transport in bulk

Not applicable

#### 14.7. Special precautions for user

##### DOT

Not regulated

##### TDG

Not regulated

##### IMDG

Not regulated

##### IATA

Not regulated

### SECTION 15 Regulatory information

#### 15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 15.2. International regulations

#### CANADA

##### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

##### Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

##### White mineral oil (petroleum) (8042-47-5)

Listed on the Canadian DSL (Domestic Substances List)

##### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

##### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

##### White mineral oil (petroleum) (8042-47-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### 15.3. State regulations



#### WARNING:

This product can expose you to Vinyl acetate, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Revision date : 5/27/2026  
Issue date : 4/29/2025  
Data sources : Supplier's safety documents.  
Training advice : Training staff on good practice.

#### Full text of hazard classes and H-statements

H304	May be fatal if swallowed and enters airways
------	--

# Synthetic Blend Marine 2-Cycle Oil

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements	
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.