



Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 4/24/2023 Revision date: 6/12/2026 Supersedes: 3/9/2026 Version: 3.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Brake Parts Cleaner
Part Number : 10906
Vaporizer : Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Cleaner, Lubricating oil

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst if heated.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity — Single exposure, Category 1	H370	Causes damage to organs.
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Hazardous to the aquatic environment — Acute Hazard, Category 2	H401	Toxic to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H222 - Extremely flammable aerosol
H229 - Pressurized container; may burst if heated
H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H370 - Causes damage to organs.
H373 - May cause damage to organs through prolonged or repeated exposure
H401 - Toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe dust, fume, gas, mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P311 - If exposed or concerned: Call a poison center or doctor.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center or doctor if you feel unwell.
P314 - Get medical advice or attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P331 - Do NOT induce vomiting.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Acetone	CAS-No.: 67-64-1	30 - 60*	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Repr. 2, H361 STOT SE 3, H336
Carbon dioxide	CAS-No.: 124-38-9	5 - 10*	Press. Gas (Liq.), H280
Heptane, branched, cyclic and linear	CAS-No.: 426260-76-6	1 - 5*	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Aquatic Chronic 2, H411
Toluene	CAS-No.: 108-88-3	1 - 5*	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Methyl Alcohol	CAS-No.: 67-56-1	0.5 - 5*	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370
Naphtha (petroleum), hydrotreated light	CAS-No.: 64742-49-0	1 - 5*	Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
Personal protection for first-aid responders.	: First-aiders should consider self-protection and use the recommended personal protective equipment (see section 8).

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. Risk of lung edema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED. Dry chemical, CO ₂ , or water spray or regular foam. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable aerosol. Pressurized container: may burst if heated. Heating may cause a fire or explosion. Extremely flammable aerosol.
Explosion hazard	: Explosion risk in case of fire. Heating may cause an explosion.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire	: Keep container tightly closed and away from heat, sparks and flame.
Firefighting instructions	: Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	--

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment. Avoid discharge to atmosphere.

6.2. Methods and materials for containment and cleaning up

For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
-----------------	---

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Obtain special instructions before use. Use only outdoors or in a well-ventilated area. Prevent the build-up of electrostatic charge. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Use only non-sparking tools. Ground/bond container and receiving equipment.
Storage conditions	: Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container closed when not in use. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Keep container tightly closed.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Acetone (67-64-1)	
USA - ACGIH® - Threshold Limit Values	
Local name	Acetone
ACGIH® TLV® TWA	250 ppm
ACGIH® TLV® STEL	500 ppm
Remark (ACGIH®)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024
USA - ACGIH® - Biological Exposure Indices	
Local name	Acetone
BEI	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL TWA	2400 mg/m³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Acetone (67-64-1)	
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Acetone [Dimethyl ketone]
Cal/OSHA PEL (OEL TWA)	1200 mg/m ³
	500 ppm
Cal/OSHA STEL	1780 mg/m ³
	750 ppm
Cal/OSHA C	3000 ppm
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Acetone
NIOSH REL 10h TWA	250 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Methyl Alcohol (67-56-1)	
USA - ACGIH® - Threshold Limit Values	
Local name	Methanol
ACGIH® TLV® TWA	262 mg/m ³
	200 ppm
ACGIH® TLV® STEL	328 mg/m ³
	250 ppm
Remark (ACGIH®)	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
USA - ACGIH® - Biological Exposure Indices	
Local name	Methanol
BEI	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Methyl alcohol
OSHA PEL TWA	260 mg/m ³
	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Methyl alcohol; methanol
Cal/OSHA PEL (OEL TWA)	260 mg/m ³
	200 ppm
Cal/OSHA STEL	325 mg/m ³
	250 ppm

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methyl Alcohol (67-56-1)	
Cal/OSHA C	1000 ppm
Remark (Cal/OSHA)	S - Skin notation and Protecting Clothing
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Methyl alcohol
NIOSH REL 10h TWA	200 ppm
NIOSH REL STEL	250 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Toluene (108-88-3)	
USA - ACGIH® - Threshold Limit Values	
Local name	Toluene
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH®)	TLV® Basis: CNS, Hearing & Visual impair; Female repro system eff; Pregnancy loss. Notations: OTO (Ototoxicant); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
USA - ACGIH® - Biological Exposure Indices	
Local name	Toluene
BEI	0.3 mg/g Kreatinin Parameter: o-Cresol - Medium: urine - Sampling time: End of shift - Notations: B 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Toluene
OSHA PEL TWA	200 ppm
OSHA PEL C	300 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Toluene; toluol
Cal/OSHA PEL (OEL TWA)	37 mg/m³
	10 ppm
Cal/OSHA STEL	560 mg/m³
	150 ppm
Cal/OSHA C	500 ppm
Remark (Cal/OSHA)	S - Skin notation and Protecting Clothing

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Toluene (108-88-3)	
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Toluene
NIOSH REL 10h TWA	100 ppm
NIOSH REL STEL	150 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-2 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Carbon dioxide (124-38-9)	
USA - ACGIH® - Threshold Limit Values	
Local name	Carbon dioxide
ACGIH® TLV® TWA	5000 ppm
ACGIH® TLV® STEL	30000 ppm
Remark (ACGIH®)	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Carbon dioxide
OSHA PEL TWA	9000 mg/m³
	5000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Carbon dioxide
NIOSH REL 10h TWA	5000 ppm
NIOSH REL STEL	30000 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Naphtha (petroleum), hydrotreated light (64742-49-0)	
USA - ACGIH® - Threshold Limit Values	
Local name	Hexane (Commercial, <54% n-hexane)
ACGIH® TLV® TWA	100 ppm
Remark (ACGIH®)	TLV® Basis: Periph neuropathy. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024

8.2. Appropriate engineering controls

Appropriate engineering controls	: Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:
Wear recommended personal protective equipment.

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following color(s): Colourless Pure substance: colourless Unpurified: light yellow
Odor	: There may be no odor warning properties, odor is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odor: Aromatic odour Sweet odour Fruity odour Characteristic odour Mild odour Pleasant odour Alcohol odour Commercial/unpurified substance: irritating/pungent odour Odourless Petroleum-like odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < 0 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: > 1
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: < 20 mm²/s
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

Gas group	: Press. Gas (Liq.)
-----------	---------------------

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Flammable aerosol. Pressurized container: may burst if heated. Extremely flammable aerosol.

10.3. Possibility of hazardous reactions

May mass explode in fire. Heating may cause a fire or explosion.

10.4. Conditions to avoid

High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Combustible materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))
LD50 oral	6667 mg/kg
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LD50 dermal	20000 mg/kg
LC50 Inhalation - Rat	132 mg/l (3 h, Rat, Male, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapors)	76 mg/l Source: ECHA
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
ATE US (vapors)	76 mg/l/4h
ATE US (dust, mist)	132 mg/l/4h
Methyl Alcohol (67-56-1)	
LD50 oral rat	1187 – 2769 mg/kg body weight (BASF test, Rat, Male / female, Experimental value, 15-35 % aqueous solution, Oral, 7 day(s))
LD50 oral	1400 mg/kg
LD50 dermal rabbit	17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LD50 dermal	15800 mg/kg

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methyl Alcohol (67-56-1)	
LC50 Inhalation - Rat	128.2 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Experimental value, Oral, 7 day(s))
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LD50 dermal	12000 mg/kg
LC50 Inhalation - Rat	28.1 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapors)	12.5 mg/l/4h
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	12000 mg/kg body weight
ATE US (vapors)	12.5 mg/l/4h
ATE US (dust, mist)	28.1 mg/l/4h
Carbon dioxide (124-38-9)	
LC50 Inhalation - Rat [ppm]	167857 ppm
Naphtha (petroleum), hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 dermal rat	2800 – 3100 mg/kg body weight Animal: rat
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	73680 ppm Source: IUCLID
ATE US (dermal)	2950 mg/kg body weight
ATE US (gases)	73680 ppmV/4h
ATE US (vapors)	73680 mg/l/4h
Skin corrosion/irritation : Not classified	
Acetone (67-64-1)	
pH	5 – 6 (20 °C)
Methyl Alcohol (67-56-1)	
pH	No data available in the literature

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Toluene (108-88-3)	
pH	No data available in the literature
Carbon dioxide (124-38-9)	
pH	3.2 Source: HSDB
Serious eye damage/irritation	: Causes serious eye irritation.
Acetone (67-64-1)	
pH	5 – 6 (20 °C)
Methyl Alcohol (67-56-1)	
pH	No data available in the literature
Toluene (108-88-3)	
pH	No data available in the literature
Carbon dioxide (124-38-9)	
pH	3.2 Source: HSDB
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male
STOT-single exposure	: Causes damage to organs. May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Methyl Alcohol (67-56-1)	
STOT-single exposure	Causes damage to organs.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Heptane, branched, cyclic and linear (426260-76-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Acetone (67-64-1)	
NOAEL (oral, rat, 90 days)	900 mg/kg bw/day
Methyl Alcohol (67-56-1)	
NOAEC (inhalation, rat, 28 days)	6.66 mg/l
NOAEC (inhalation, rat, 90 days)	1.06 mg/l

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	1250 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapor, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Naphtha (petroleum), hydrotreated light (64742-49-0)	
LOAEC (inhalation, rat, vapor, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation, rat, vapor, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male

Aspiration hazard : May be fatal if swallowed and enters airways.

Brake Parts Cleaner	
Vaporizer	Aerosol
Viscosity, kinematic	< 20 mm²/s

Acetone (67-64-1)	
Viscosity, kinematic	No data available in the literature

Methyl Alcohol (67-56-1)	
Viscosity, kinematic	0.68 – 0.747 mm²/s

Toluene (108-88-3)	
Viscosity, kinematic	No data available in the literature

Naphtha (petroleum), hydrotreated light (64742-49-0)	
Viscosity, kinematic	0.67 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion : May cause irritation to the digestive tract. Risk of lung edema.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
EC50 - Crustacea [1]	12600 – 12700 mg/l
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methyl Alcohol (67-56-1)	
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
ErC50 algae	20300 mg/l
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'
Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	3.78 mg/l
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
NOEC chronic crustacea	0.74 mg/l
Carbon dioxide (124-38-9)	
LC50 - Fish [1]	35 mg/l (96 h, Salmo gairdneri, Lethal)
Naphtha (petroleum), hydrotreated light (64742-49-0)	
LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
12.2. Persistence and degradability	
Brake Parts Cleaner	
Persistence and degradability	Not rapidly degradable
Acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
Methyl Alcohol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance

Heptane, branched, cyclic and linear (426260-76-6)	
Persistence and degradability	Not rapidly degradable

Carbon dioxide (124-38-9)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Naphtha (petroleum), hydrotreated light (64742-49-0)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Partition coefficient n-octanol/water (Log Kow)	-0.23
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Methyl Alcohol (67-56-1)	
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Toluene (108-88-3)	
BCF - Fish [1]	90 (3 day(s), Leuciscus idus, Static renewal, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Carbon dioxide (124-38-9)	
Partition coefficient n-octanol/water (Log Pow)	0.83 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Naphtha (petroleum), hydrotreated light (64742-49-0)	
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID

12.4. Mobility in soil

Acetone (67-64-1)	
Surface tension	23.3 mN/m (20 °C)

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Acetone (67-64-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Methyl Alcohol (67-56-1)	
Mobility in soil	2.75 Source: HSDB
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
Toluene (108-88-3)	
Surface tension	27.73 mN/m (25 °C, 0.05 %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.3 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1950	UN1950	UN1950	UN1950
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

DOT	TDG	IMDG	IATA
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT	
UN-No. (DOT)	: UN1950
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed “on deck” or “under deck” on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Shade from radiant heat,87 - Stow “separated from” Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials
TDG	
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment),107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126
IMDG	
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA

Special provision (IATA)	: A145, A167, A802
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
ERG code (IATA)	: 10L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methyl Alcohol	CAS-No. 67-56-1	0.5 - 5*%
Toluene	CAS-No. 108-88-3	1 - 5*%

Acetone (67-64-1)

CERCLA RQ	5000 lb
-----------	---------

Methyl Alcohol (67-56-1)

Listed on EPA Hazardous Air Pollutant (HAPS)
Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits

CERCLA RQ	5000 lb
-----------	---------

Toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)
Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methyl Alcohol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

Heptane, branched, cyclic and linear (426260-76-6)

Listed on the Canadian DSL (Domestic Substances List)

Carbon dioxide (124-38-9)

Listed on the Canadian DSL (Domestic Substances List)

Naphtha (petroleum), hydrotreated light (64742-49-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Acetone (67-64-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Methyl Alcohol (67-56-1)

Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Toluene (108-88-3)

Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Carbon dioxide (124-38-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Naphtha (petroleum), hydrotreated light (64742-49-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations



WARNING:

This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Revision date : 6/12/2026

Brake Parts Cleaner

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date : 4/24/2023

Full text of hazard classes and H-statements	
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H229	Pressurized container; may burst if heated
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.