

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 8/4/2025 Revision date: 5/11/2026 Supersedes: 3/4/2026 Version: 3.0

SECTION 1 Identification**1.1. Product identifier**

Product form : Mixture
Product name : Marine Automatic Transmission Fluid Type F
Part Number : 11099

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Lubricating oil

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

SECTION 2 Hazard Identification**2.1. Classification of the substance or mixture****GHS US classification**

Reproductive toxicity, Category 2 H361 Suspected of damaging fertility or the unborn child.
Full text of H statements : see section 16

2.2. Label elements**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H361 - Suspected of damaging fertility or the unborn child
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	65 - 85*	Asp. Tox. 1, H304
1-Decene, homopolymer, hydrogenated	CAS-No.: 68037-01-4	3 - 7*	Asp. Tox. 1, H304
1-Dodecene, polymer with 1-decene, hydrogenated	CAS-No.: 151006-60-9	3 - 7*	Asp. Tox. 1, H304
1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated	CAS-No.: 68649-12-7	3 - 7*	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light naphthenic	CAS-No.: 64742-53-6	1 - 5*	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	1 - 5*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Toluene	CAS-No.: 108-88-3	0.086 - 0.428	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Take off contaminated clothing. Get medical attention if symptoms occur. Wash skin with plenty of water.
First-aid measures after eye contact	: When in doubt or if symptoms are observed, get medical advice. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth out with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a poison center/doctor/physician if you feel unwell.

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Personal protection for first-aid responders. : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.

Symptoms/effects after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

Chronic symptoms : Suspected of damaging fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard. In case of fire and/or explosion do not breathe fumes.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate area. Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methods for cleaning up	: Take up liquid spill into absorbent material. Move containers from spill area. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep only in the original container in a cool, well-ventilated place away from: Direct sunlight, Heat sources. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store locked up.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Toluene (108-88-3)	
USA - ACGIH® - Threshold Limit Values	
Local name	Toluene
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH®)	TLV® Basis: CNS, Hearing & Visual impair; Female repro system eff; Pregnancy loss. Notations: OTO (Ototoxicant); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
USA - ACGIH® - Biological Exposure Indices	
Local name	Toluene
BEI	0.3 mg/g Kreatinin Parameter: o-Cresol - Medium: urine - Sampling time: End of shift - Notations: B 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Toluene
OSHA PEL TWA	200 ppm
OSHA PEL C	300 ppm

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Toluene (108-88-3)	
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Toluene; toluol
Cal/OSHA PEL (OEL TWA)	37 mg/m ³
	10 ppm
Cal/OSHA STEL	560 mg/m ³
	150 ppm
Cal/OSHA C	500 ppm
Remark (Cal/OSHA)	S - Skin notation and Protecting Clothing
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Toluene
NIOSH REL 10h TWA	100 ppm
NIOSH REL STEL	150 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-2 (NIOSH Pocket Guide to Chemical Hazards (NPG))
1-Decene, homopolymer, hydrogenated (68037-01-4)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	5 mg/m ³ (Inhalable fraction)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety procedures. Ensure exposure is below occupational exposure limits (where available). Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. [In case of inadequate ventilation] wear respiratory protection.

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.841
Density	: 7.02 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 41.6 mm ² /s @ 40 ° C
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	5000 mg/kg
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	5000 mg/kg body weight

1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)

LD50 oral rat	> 5000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 3000 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapors)	0.9 mg/l Source: ECHA
ATE US (vapors)	0.9 mg/l/4h

Toluene (108-88-3)

LD50 oral rat	5580 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Experimental value, Oral, 7 day(s))
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LD50 dermal	12000 mg/kg
LC50 Inhalation - Rat	28.1 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapors)	12.5 mg/l/4h
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	12000 mg/kg body weight
ATE US (vapors)	12.5 mg/l/4h
ATE US (dust, mist)	28.1 mg/l/4h

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
LD50 dermal	2500 mg/kg
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	2500 mg/kg body weight
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
1-Decene, homopolymer, hydrogenated (68037-01-4)	
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Not classified
1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)	
pH	3.9 Source: ECHA
Toluene (108-88-3)	
pH	No data available in the literature
Serious eye damage/irritation	: Not classified
1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)	
pH	3.9 Source: ECHA
Toluene (108-88-3)	
pH	No data available in the literature
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,dust/mist/fume,90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Toluene (108-88-3)	
LOAEL (oral,rat,90 days)	1250 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral,rat,90 days)	625 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation,rat,vapor,90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified

Marine Automatic Transmission Fluid Type F	
Viscosity, kinematic	41.6 mm ² /s @ 40 ° C

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Viscosity, kinematic	12 mm ² /s
Hydrocarbon	Yes

Toluene (108-88-3)	
Viscosity, kinematic	No data available in the literature

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
Viscosity, kinematic	2 mm ² /s @ 40 ° C

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	18 mm ² /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
Chronic symptoms	: Suspected of damaging fertility or the unborn child.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)	
LC50 - Fish [1]	> 1000 mg/l Source: e-ChemPortal;HPVIS
EC50 96h - Algae [1]	> 1000 mg/l Source: e-ChemPortal;HPVIS
Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	3.78 mg/l
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
NOEC chronic crustacea	0.74 mg/l
Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID
12.2. Persistence and degradability	
Marine Automatic Transmission Fluid Type F	
Persistence and degradability	Biodegradability in water: no data available.
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Persistence and degradability	Not rapidly degradable
1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)	
Persistence and degradability	Not rapidly degradable
1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)	
Persistence and degradability	Not rapidly degradable
Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
Persistence and degradability	Not rapidly degradable
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
1-Decene, homopolymer, hydrogenated (68037-01-4)	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

Marine Automatic Transmission Fluid Type F	
Bioaccumulative potential	No data available concerning bioaccumulation.
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)	
Partition coefficient n-octanol/water (Log Pow)	7.64 Source: e-ChemPortal;HPVIS
1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)	
Partition coefficient n-octanol/water (Log Pow)	5
Toluene (108-88-3)	
BCF - Fish [1]	90 (3 day(s), Leuciscus idus, Static renewal, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
1-Decene, homopolymer, hydrogenated (68037-01-4)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

Marine Automatic Transmission Fluid Type F	
Ecology - soil	No additional information available.
1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)	
Mobility in soil	192200000 Source: EPISUITE
Toluene (108-88-3)	
Surface tension	27.73 mN/m (25 °C, 0.05 %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.3 (log Koc, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

IMDG
Not regulated

IATA
Not regulated

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS-No. 108-88-3	0.086 - 0.428%
---------	------------------	----------------

Toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)
Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)

Listed on the Canadian DSL (Domestic Substances List)

1-Dodecene, polymer with 1-decene, hydrogenated (151006-60-9)

Listed on the Canadian DSL (Domestic Substances List)

Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

1-Decene, homopolymer, hydrogenated (68037-01-4)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Marine Automatic Transmission Fluid Type F

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

National regulations

Toluene (108-88-3)

Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens
Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

1-Decene, homopolymer, hydrogenated (68037-01-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations



WARNING:

This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Revision date	: 5/11/2026
Issue date	: 8/4/2025
Data sources	: Supplier's safety documents.
Training advice	: Training staff on good practice.

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.