

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : TIRE INFLATOR (SEALS & INFLATES) :
Product code 11180

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Flat Fix

1.3. Details of the supplier of the safety data sheet

Lucas Oil Products
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800.342.2512 - F 951.270.1902
www.lucasoil.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1	H222;H229	Pressurized container; may burst if heated.
Gases under pressure : Compressed gas	H280	Contains gas under pressure; may explode if heated.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Carcinogenicity, Category 1A	H350	May cause cancer.

Full text of H- and EUH-statements: see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H229 - Pressurized container; may burst if heated
H280 - Contains gas under pressure; may explode if heated
H319 - Causes serious eye irritation
H350 - May cause cancer.

Precautionary statements (GHS US) :

P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce, or burn, even after use.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards

Other hazards which do not result in classification : Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Water	(CAS-No.) 7732-18-5	40-65	Not classified
Polymer Latex	(CAS-No.) Proprietary	10 – 30	Eye Irrit. 2B, H320
Trans-1,3,3,3-tetrafluoroprop-1-ene	(CAS-No.) 29118-24-9	10 – 30	Press. Gas (Liq.), H280
R152 (1,1-difluoroethane)	(CAS-No.) 75-37-6	10 – 30	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Ethanol	(CAS-No.) 64-17-5	1 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Carc. 1A, H350
2-Propanol	(CAS-No.) 67-63-0	1 – 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
2-Aminoethanol	(CAS-No.) 141-43-5	≤ 0.691	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1, H314
Ammonium Hydroxide, Aqueous Solution, Conc=25%	(CAS-No.) 1336-21-6	< 1	Skin Corr. 1B, H314 Aquatic Acute 1, H400

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : If you feel unwell, seek medical advice.
- Symptoms/effects after inhalation : May cause cancer by inhalation.
- Symptoms/effects after skin contact : Frostbites. Itching. May cause slight irritation . Red skin. Skin rash/inflammation.
- Symptoms/effects after eye contact : Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.
- Symptoms/effects after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Explosion hazard : Contains gas under pressure; may explode if heated.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : NFPA Aerosol Level 1.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released product, collect/pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions . Do not handle until all safety precautions have been read and understood.
Hygiene measures : Do not eat, drink or smoke when using this product. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.
Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

LUCAS TIRE INFLATOR (SEALS & INFLATES) 16 OZ.	
No additional information available	
Water (7732-18-5)	
No additional information available	
2-Aminoethanol (141-43-5)	
No additional information available	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	3 ppm
ACGIH OEL STEL	6 ppm
Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)	
No additional information available	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	24 ppm
ACGIH OEL STEL	35 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	50 ppm
2-Propanol (67-63-0)	
No additional information available	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	980 mg/m ³
	400 ppm
ACGIH OEL STEL	1225 mg/m ³
	500 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	980 mg/m ³
	400 ppm

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	980 mg/m ³
	400 ppm
NIOSH REL (Ceiling)	1225 mg/m ³
	500 ppm
Polymer Latex (Proprietary)	
No additional information available	
Ethanol (64-17-5)	
No additional information available	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL STEL	1000 ppm
Trans-1,3,3,3-tetrafluoroprop-1-ene (29118-24-9)	
No additional information available	
R152 (1,1-difluoroethane) (75-37-6)	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

Materials for protective clothing:

Excellent resistance:

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.
Color : White.
Odor : Mild ammonia.
Odor threshold : No data available
pH : 9 – 10
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point	: > 60 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.99 – 1
Solubility	: Soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Heating may cause an explosion.
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

VOC content	: 5.1 %
Gas group	: Compressed gas

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-Aminoethanol (141-43-5)	
LD50 oral rat	1089 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	2504 – 2881 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 1.3 mg/l air (6 h, Rat, Male / female, Experimental value, (maximum achievable concentration), Inhalation (vapours), 14 day(s))
ATE US (oral)	1089 mg/kg body weight
ATE US (dermal)	2504 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h
2-Propanol (67-63-0)	
LD50 oral rat	5840 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	5840 mg/kg body weight
ATE US (dermal)	12890400 mg/kg body weight

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg body weight (Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	125 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	10470 mg/kg body weight
ATE US (vapors)	125 mg/l/4h
ATE US (dust, mist)	125 mg/l/4h

Trans-1,3,3,3-tetrafluoroprop-1-ene (29118-24-9)	
LC50 Inhalation - Rat	> 965 mg/l (4 h, Rat, Read-across, Inhalation (gases))
LC50 Inhalation - Rat [ppm]	> 359300 ppm (4 h, Rat, Read-across, Inhalation)

Skin corrosion/irritation	: Not classified pH: 9 – 10
Serious eye damage/irritation	: Causes serious eye irritation. pH: 9 – 10
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

2-Propanol (67-63-0)	
IARC group	3 - Not classifiable

Ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

2-Propanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	: Not classified
Aspiration hazard	: Not applicable
Viscosity, kinematic	: No data available
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: If you feel unwell, seek medical advice.
Symptoms/effects after inhalation	: May cause cancer by inhalation.
Symptoms/effects after skin contact	: Frostbites. Itching. May cause slight irritation . Red skin. Skin rash/inflammation.
Symptoms/effects after eye contact	: Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.
Symptoms/effects after ingestion	: May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

2-Aminoethanol (141-43-5)	
LC50 - Fish [1]	349 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	27 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	2.8 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

2-Propanol (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

Polymer Latex (Proprietary)	
LC50 - Fish [1]	> 1000 mg/l Toxicity to fish sludge (96 hours) (Carp)

Ethanol (64-17-5)	
LC50 - Fish [1]	15300 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Trans-1,3,3,3-tetrafluoroprop-1-ene (29118-24-9)

LC50 - Fish [1]	> 117 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Cyprinus carpio, Static system, Fresh water, Experimental value, Similar product)
EC50 - Crustacea [1]	> 160 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Similar product)
ErC50 algae	> 170 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Similar product)

12.2. Persistence and degradability

LUCAS TIRE INFLATOR (SEALS & INFLATES) 16 OZ.

Persistence and degradability	Not established.
-------------------------------	------------------

Water (7732-18-5)

Persistence and degradability	Not established.
-------------------------------	------------------

2-Aminoethanol (141-43-5)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Not established.
Biochemical oxygen demand (BOD)	0.8 g O ₂ /g substance
Chemical oxygen demand (COD)	1.34 g O ₂ /g substance
ThOD	2.49 g O ₂ /g substance

Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the components available. Ozonation in the air. Not established.
-------------------------------	--

2-Propanol (67-63-0)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. Not established.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance

Polymer Latex (Proprietary)

Persistence and degradability	Not established.
-------------------------------	------------------

Ethanol (64-17-5)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil. Not established.
Biochemical oxygen demand (BOD)	0.8 – 0.967 g O ₂ /g substance
Chemical oxygen demand (COD)	1.7 g O ₂ /g substance
ThOD	2.1 g O ₂ /g substance

Trans-1,3,3,3-tetrafluoroprop-1-ene (29118-24-9)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

R152 (1,1-difluoroethane) (75-37-6)

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

LUCAS TIRE INFLATOR (SEALS & INFLATES) 16 OZ.

Bioaccumulative potential	Not established.
---------------------------	------------------

Water (7732-18-5)

Bioaccumulative potential	Not established.
---------------------------	------------------

2-Aminoethanol (141-43-5)

Partition coefficient n-octanol/water (Log Pow)	-2.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.

Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)

Bioaccumulative potential	Not bioaccumulative. Not established.
---------------------------	---------------------------------------

2-Propanol (67-63-0)

BCF - Fish [1]	1015 (BCFBAF v3.01, Estimated value)
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.

Polymer Latex (Proprietary)

Bioaccumulative potential	Not established.
---------------------------	------------------

Ethanol (64-17-5)

Partition coefficient n-octanol/water (Log Pow)	-0.35 (Experimental value, Equivalent or similar to OECD 107, 24 °C)
---	--

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol (64-17-5)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.
Trans-1,3,3,3-tetrafluoroprop-1-ene (29118-24-9)	
Partition coefficient n-octanol/water (Log Pow)	1.6 (Similar product, Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
R152 (1,1-difluoroethane) (75-37-6)	
Partition coefficient n-octanol/water (Log Pow)	1.13
Partition coefficient n-octanol/water (Log Kow)	No Data Available
Bioaccumulative potential	Not established.

12.4. Mobility in soil

2-Aminoethanol (141-43-5)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.2 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the component(s) available.
2-Propanol (67-63-0)	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C, 100 %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.2 (log Koc, Experimental value)
Ecology - soil	Highly mobile in soil.
Trans-1,3,3,3-tetrafluoroprop-1-ene (29118-24-9)	
Ecology - soil	Not applicable (gas).
R152 (1,1-difluoroethane) (75-37-6)	
Mobility in soil	No data available

12.5. Other adverse effects

Effect on global warming : No known effects from this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecological information : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT


Transport document description (DOT) : UN1950 Aerosols, Non-flammable (Non-flammable, (each not exceeding 1 L capacity)), 2.2, Limited Quantity
UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols, Non-flammable
Non-flammable, (each not exceeding 1 L capacity)
Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : LTD QTY - Limited quantity



DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Other information : No supplementary information available.

Transport by sea

UN-No. (IMDG) : 1950

Proper Shipping Name (IMDG) : Aerosols, Non-flammable

Class (IMDG) : 2.2 - Non-flammable, non-toxic gases

Air transport

UN-No. (IATA) : 1950

Proper Shipping Name (IATA) : Aerosols, Non-flammable

Class (IATA) : 2.2 - Gases : Non-flammable, non-toxic

Hazard labels (IATA) : LTD QTY - Limited Quantity



SECTION 15: Regulatory information

15.1. US Federal regulations

LUCAS TIRE INFLATOR (SEALS & INFLATES) 16 OZ.	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Sudden release of pressure hazard
2-Aminoethanol (141-43-5)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
2-Propanol (67-63-0)	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
SARA Section 313 - Emission Reporting	1 %
Polymer Latex (Proprietary)	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	
Trans-1,3,3,3-tetrafluoroprop-1-ene (29118-24-9)	
EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance.

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

LUCAS TIRE INFLATOR (SEALS & INFLATES) 16 OZ.	
WHMIS Classification	Class A - Compressed Gas
Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)	
Listed on the Canadian DSL (Domestic Substances List)	
2-Propanol (67-63-0)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Listed on INSQ (Mexican National Inventory of Chemical Substances)	
2-Propanol (67-63-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Listed on INSQ (Mexican National Inventory of Chemical Substances)	
Polymer Latex (Proprietary)	
Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)	

15.3. US State regulations

LUCAS TIRE INFLATOR (SEALS & INFLATES) 16 OZ.()				
U.S. - California - Proposition 65 - Carcinogens List		No		
U.S. - California - Proposition 65 - Developmental Toxicity		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		No		
State or local regulations		U.S. - California - Proposition 65		
Water (7732-18-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
2-Aminoethanol (141-43-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
2-Propanol (67-63-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 -	U.S. - California - Proposition 65 -	No significant risk level (NSRL)

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Propanol (67-63-0)				
		Reproductive Toxicity - Female	Reproductive Toxicity - Male	
No	No	No	No	
Polymer Latex (Proprietary)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
Ethanol (64-17-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
Trans-1,3,3,3-tetrafluoroprop-1-ene (29118-24-9)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
R152 (1,1-difluoroethane) (75-37-6)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
2-Aminoethanol (141-43-5)				
State or local regulations				
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York City - Right to Know Hazardous Substances List U.S. - Pennsylvania - RTK (Right to Know) List				
Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)				
State or local regulations				
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS) U.S. - New York City - Right to Know Hazardous Substances List U.S. - Pennsylvania - RTK (Right to Know) List				
2-Propanol (67-63-0)				
State or local regulations				
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York City - Right to Know Hazardous Substances List U.S. - Pennsylvania - RTK (Right to Know) List				
Ethanol (64-17-5)				
State or local regulations				
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York City - Right to Know Hazardous Substances List U.S. - Pennsylvania - RTK (Right to Know) List				

TIRE INFLATOR (SEALS & INFLATES)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

R152 (1,1-difluoroethane) (75-37-6)
State or local regulations
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York City - Right to Know Hazardous Substances List


SECTION 16: Other information

Other information : None.

Full text of hazard classes and H-statements:

H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H229	Pressurized container; may burst if heated
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H350	May cause cancer.
H400	Very toxic to aquatic life

- NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
- NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

- Health : 1 Slight Hazard - Irritation or minor reversible injury possible
- Flammability : 1 Slight Hazard
- Physical : 1 Slight Hazard
- Personal protection : B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.