

SECTION 1 Identification**1.1. GHS Product identifier**

Product form	: Mixture
Product name	: SAE 5W-20 Motor Oil
Type of product	: Lubricating oil
Part Number	: 18001

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	: Lubricating oil
Recommended use	: Lubricating oil
Restrictions on use	: No additional information available

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number	: For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.
------------------	---

SECTION 2 Hazard identification**2.1. Classification of the substance or mixture****Classification (GHS CA)**

Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Hazardous to the aquatic environment, Chronic Hazard, Category 4	H413	May cause long lasting harmful effects to aquatic life.
Full text of H-statements: see section 16		

2.2. GHS label elements, including precautionary statements**GHS CA labelling**

Hazard pictograms (GHS CA)



Signal word (GHS CA)

: Warning

Hazard statements (GHS CA)

: H317 - May cause an allergic skin reaction
H361 - Suspected of damaging fertility or the unborn child
H413 - May cause long lasting harmful effects to aquatic life

SAE 5W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Precautionary statements (GHS CA) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust, fume, gas, mist, vapours, spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P308+P313 - IF exposed or concerned: Get medical advice or attention.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	80 - 100*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Benzenamine, ar-nonyl-N-(nonylphenyl)-	ar-Nonyl-N-(nonylphenyl)benzenamine	CAS-No.: 36878-20-3	0.5 - 1.5*	Repr. 2, H361 Aquatic Chronic 4, H413
Calcium long chain alkaryl sulfonate	-	CAS-No.: 722503-69-7	0.1 - 1*	Skin Sens. 1, H317

*Chemical name, CAS number and/or exact concentration have been withheld as CBI

*Contains fixed concentration

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

SAE 5W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
Self protection of the first-aiders : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : May cause an allergic skin reaction.
Symptoms/effects after eye contact : None under normal conditions.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.
For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

SAE 5W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up.
Packaging materials	: Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: No data available
Odour	: No data available

SAE 5W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.851
Density	: 7.109 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 48.03 mm ² /s @ 40 ° C
Explosive limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
--------------------	-----------------------------

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified

SAE 5W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

STOT-repeated exposure : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified.

SAE 5W-20 Motor Oil	
Viscosity, kinematic	48.03 mm ² /s @ 40 ° C

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	18 mm ² /s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : May cause an allergic skin reaction.
Symptoms/effects after eye contact : None under normal conditions.
Symptoms/effects after ingestion : None under normal conditions.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : May cause long lasting harmful effects to aquatic life.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : May cause long lasting harmful effects to aquatic life.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
LC50 - Fish [1]	> 0.0013 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

SAE 5W-20 Motor Oil	
Persistence and degradability	Biodegradability in water: no data available.

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Persistence and degradability	Not rapidly degradable

Calcium long chain alkaryl sulfonate (722503-69-7)	
Persistence and degradability	Not rapidly degradable

SAE 5W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

12.3. Bioaccumulative potential

SAE 5W-20 Motor Oil

Bioaccumulative potential	No data available concerning bioaccumulation.
---------------------------	---

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

12.4. Mobility in soil

SAE 5W-20 Motor Oil

Ecology - soil	No additional information available.
----------------	--------------------------------------

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Mobility in soil	35900000 Source: EPISUITE
------------------	---------------------------

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
Not regulated for transport			
14.2. UN Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group, if applicable			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

SAE 5W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

14.6. Special precautions for user

TDG

Not regulated

DOT

Not regulated

IMDG

Not regulated

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78⁹ and the IBC Code¹⁰

Not applicable

SECTION 15 Regulatory information

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Listed on the Canadian DSL (Domestic Substances List)

Calcium long chain alkaryl sulfonate (722503-69-7)

Listed on the Canadian NDSL (Non-Domestic Substances List)

SAE 5W-20 Motor Oil

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Calcium long chain alkaryl sulfonate (722503-69-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

SECTION 16 Other Information

Issue date : 04/30/2025

Revision date : 05/06/2026

Supersedes : 05/01/2026

Data sources : Supplier's safety documents.

SAE 5W-20 Motor Oil

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)

Training advice : Training staff on good practice.

Full text of hazard classes and H-statements:	
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H361	Suspected of damaging fertility or the unborn child
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.