RED “N” TACKY® Spray Grease

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015)
Issue date: 03/04/2025 Revision date: 07/16/2026 Supersedes: 07/07/2026 Version: 4.0

SECTION 1 Identification

1.1. GHS Product identifier

Product form	: Mixture
Product name	: RED “N” TACKY® Spray Grease
Part Number	: 21025
Vaporizer	: Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : lubricants

1.4. Supplier's details

Lucas Oil Products, Inc.
3199 Harrison Way NW
Corydon, IN 47112
USA
T 800-342-2512
sds@lucasoil.com - www.LucasOil.com

1.5. Emergency phone number

Emergency number : For Chemical Emergency Call ChemTel 24hr/day 7days/week. Within USA, Canada, Puerto Rico & US Virgin Islands: 1-800-255-3924. International: 1-813-248-0585 (collect calls accepted). Australia: 1-300-954-583. Brazil: 0-800-591-6042. China: 400-120-0751. India: 000-800-100-4086. Mexico: 800-099-0731.

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst if heated.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Hazardous to the aquatic environment, Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H-statements: see section 16

2.2. GHS label elements, including precautionary statements

GHS CA labelling

Hazard pictograms (GHS CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS CA)	:	H222 - Extremely flammable aerosol H229 - Pressurized container; may burst if heated H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H361 - Suspected of damaging fertility or the unborn child H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS CA)	:	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing dust, fume, gas, mist, vapours, spray. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor. P302+P352 - IF ON SKIN: Wash with plenty of water. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice or attention. P312 - Call a POISON CENTER or a doctor if you feel unwell. P321 - Specific treatment (see supplemental first aid instruction on this label). P331 - Do NOT induce vomiting. P333+P313 - If skin irritation or rash occurs: Get medical advice or attention. P337+P313 - If eye irritation persists: Get medical advice or attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Acetic acid, methyl ester	Methyl acetate; Acetic acid methyl ester acetate of methyl / acetic acid methyl ester / acetic acid, methyl ester / devoton / ethyl ester of monoacetil acid / methyl acetate / methyl acetate, anhydrous / methyl acetic ester / methyl ester acetic acid / methyl ethanoate / tereton	CAS-No.: 79-20-9	15 - 40*	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-Methylpentane	2-Methylpentane 2-methylpentane / dimethylpropylmethane / i-hexane / isocaproyl hydride / isohexane / isohexyl hydride / methylpentane (=2-methylpentane) / pentane, 2-methyl-	CAS-No.: 107-83-5	10 - 30*	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	Benzenesulfonic acid alkyl(C=10-16) derivs., calcium salt	CAS-No.: 68584-23-6	1 - 5*	Skin Sens. 1B, H317

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Pentane	Pentane AD3/AD4-51 / alkane C5 / C5 pentane / normal-pentane / normal-pentane, commercial / normal-pentane, polymerization / normal-pentane, pure / normal-pentane, research / norpar 5 / n-pentane / pentane / pentane 75 / pentane, anhydrous / pentane, commercial / pentane, normal / pentane, pure grade / R-601 / skellysolve A	CAS-No.: 109-66-0	1 - 5*	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Distillates (petroleum), hydrotreated heavy paraffinic	Distillates (petroleum), hydrotreated heavy paraffinic distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	1 - 5*	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
Hexane	n-Hexane ; Hexane dipropyl / gettysolve-B / hex (=normal-hexane) / hexane- / hexane, anhydrous / hexane,pure grade / hexyl hydride / high purity normal hexane / n-caproylhydride / n-hexane / n-hexyl hydride / normal-caproyl hydride / normal-hexane / normal-hexyl hydride / skellysolve B / solvent hexane	CAS-No.: 110-54-3	0.1 - 1*	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Benzenamine, ar-nonyl-N-(nonylphenyl)-	ar-Nonyl-N-(nonylphenyl)benzenamine	CAS-No.: 36878-20-3	0.1 - 1*	Repr. 2, H361 Aquatic Chronic 4, H413
1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis-	5,5"-Dithiodi-1,3,4-thiadiazole-2(3H)-thione	CAS-No.: 72676-55-2	0.1 - 1*	Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Sulfonic acids, petroleum, calcium salts	Sulfonic acids, petroleum, calcium salt	CAS-No.: 61789-86-4	0.009	Skin Sens. 1B, H317

***Chemical name, CAS number and/or exact concentration have been withheld as CBI**
***Contains fixed concentration**

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.
First-aid measures general : Call a physician immediately.
Self protection of the first-aider : First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion : May cause irritation to the digestive tract. Risk of lung oedema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5 Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED. Dry chemical, CO2, or water spray or regular foam. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol. Pressurised container: May burst if heated. Heating may cause a fire or explosion.
Explosion hazard : Explosion risk in case of fire. Heating may cause an explosion.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective actions for fire-fighters

Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

Precautionary measures fire : Keep container tightly closed and away from heat, sparks and flame.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

Personal Precautions, Protective Equipment and Emergency Procedures : Self-contained breathing apparatus.

Environmental precautions : Avoid release to the environment. Avoid discharge to atmosphere.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Use only outdoors or in a well-ventilated area. Prevent the build-up of electrostatic charge. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use only non-sparking tools. Ground/bond container and receiving equipment.

Storage conditions : Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container closed when not in use. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Keep container tightly closed.

Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Acetic acid, methyl ester (79-20-9)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Methyl acetate

Acetic acid, methyl ester (79-20-9)	
OEL TWA	606 mg/m³
	200 ppm
OEL STEL	757 mg/m³
	250 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Methyl acetate
VECD (OEL STEV)	757 mg/m³
	250 ppm
VEMP (OEL TWAEV)	606 mg/m³
	200 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA	200 ppm
OEL STEL	250 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2024
Canada (New Brunswick) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	eye & URT irr
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2024

Acetic acid, methyl ester (79-20-9)	
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2024
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA	200 ppm
OEL STEL	250 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA	200 ppm
OEL STEL	250 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWAEV	200 ppm
	250 ppm
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA	200 ppm
OEL STEL	250 ppm
Notations and remarks	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
Regulatory reference	ACGIH 2024
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Methyl acetate
OEL TWA	200 ppm
OEL STEL	250 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

2-Methylpentane (107-83-5)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	2-Methylpentane (Hexane (all isomers except n-hexane, isohexane))

2-Methylpentane (107-83-5)	
OEL TWA	1760 mg/m³
	500 ppm
OEL STEL	3500 mg/m³
	1000 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Hexane, all isomers except n-Hexane
OEL TWA	200 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	2-Methyl pentane
OEL TWA	200 ppm
Notations and remarks	TLV® Basis: URT irr; lung dam. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	2-Methyl pentane
OEL TWA	200 ppm
Notations and remarks	TLV® Basis: URT irr; lung dam. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	2-Methyl pentane
OEL TWA	200 ppm
Notations and remarks	TLV® Basis: URT irr; lung dam. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
Canada (Ontario) - Occupational Exposure Limits	
Local name	Hexane isomers, other than n-Hexane
OEL TWAEV	500 ppm
	1000 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	2-Methyl pentane
OEL TWA	200 ppm
Notations and remarks	TLV® Basis: URT irr; lung dam. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)

2-Methylpentane (107-83-5)	
Regulatory reference	ACGIH 2025

Pentane (109-66-0)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Pentane, all isomers
OEL TWA	1770 mg/m³
	600 ppm
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	Pentane (all isomers)
VEMP (OEL TWAEV)	1000 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Pentane, all isomers
OEL TWA	1000 ppm
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Pentane
OEL TWA	2950 mg/m³
	1000 ppm
Notations and remarks	TLV® Basis: Narcosis; resp tract irr
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Pentane
OEL TWA	2950 mg/m³
	1000 ppm
Notations and remarks	TLV® Basis: Narcosis; resp tract irr
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Pentane
OEL TWA	2950 mg/m³
	1000 ppm
Notations and remarks	TLV® Basis: Narcosis; resp tract irr
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Pentane, all isomers
OEL TWA	600 ppm
OEL STEL	750 ppm

Pentane (109-66-0)	
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Pentane, all isomers
OEL TWA	600 ppm
OEL STEL	750 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	Pentane, All isomers
OEL TWAEV	1000 ppm
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Pentane
OEL TWA	2950 mg/m³
	1000 ppm
Notations and remarks	TLV® Basis: Narcosis; resp tract irr
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Pentane, all isomers
OEL TWA	600 ppm
OEL STEL	750 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

Hexane (110-54-3)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m³
	50 ppm
Notations and remarks	Substance may be readily absorbed through intact skin.
Regulatory reference	Alberta Regulation 191/2021
Canada (Quebec) - Occupational Exposure Limits	
Local name	n-Hexane
VEMP (OEL TWAEV)	176 mg/m³
	50 ppm
Notations and remarks	Pc
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (British Columbia) - Occupational Exposure Limits	
Local name	n-Hexane

Hexane (110-54-3)	
OEL TWA	20 ppm
Notations and remarks	Skin (the substance that contribute significantly to the overall exposure by the skin route)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m³
	50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m³
	50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m³
	50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-090-2024)
Canada (Ontario) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWAEV	50 ppm
Notations and remarks	Skin

Hexane (110-54-3)	
Regulatory reference	Occupational Health and Safety Act, R.S.O. 1990, c. O.1 - R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	n-Hexane
OEL TWA	176 mg/m³
	50 ppm
Notations and remarks	TLV® Basis: CNS impair; Peripheral neuropathy; Eye & URT irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Hexane (n-Hexane)
OEL TWA	50 ppm
OEL STEL	62.5 ppm
Notations and remarks	Skin
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:
Wear recommended personal protective equipment.

Hand protection:
Protective gloves

Eye protection:
Safety glasses

Skin and body protection:
Wear suitable protective clothing

Respiratory protection:
Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Liquid
Appearance	:	No data available
Colour	:	Colourless
Odour	:	petroleum-like odour
Odour threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available
Relative evaporation rate (ether=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	-104 °C (Propane)
Auto-ignition temperature	:	450 °C (Propane)
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Not applicable
Vapour pressure	:	95000 Pa (Propane) @ 20 ° C
Relative vapour density at 20°C	:	No data available
Relative density	:	No data available
Density	:	1.56 @ 0 ° C (Propane)
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	< 20.5 mm²/s @ 40 ° C
Explosive limits	:	Lower explosion limit: 2.1 Vol-% (Propane) Upper explosion limit: 9.5 Vol-% (Propane)
Particle characteristics	:	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

Gas group	:	Press. Gas (Liq.)

SECTION 10 Stability and reactivity

Reactivity	:	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	:	Extremely flammable aerosol. Pressurised container: May burst if heated.
Possibility of hazardous reactions	:	May mass explode in fire. Heating may cause a fire or explosion.
Conditions to avoid	:	High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	:	Combustible materials.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	:	No additional information available

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
LD50 oral rat	> 16000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
LD50 dermal rabbit	> 4000 mg/kg bodyweight Animal: rabbit, Guideline: other:

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
LD50 oral rat	> 16000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:
LD50 dermal rat	> 2000 mg/kg Source: International Uniform ChemicaL Information Database
LD50 dermal rabbit	> 4000 mg/kg bodyweight Animal: rabbit, Guideline: other:
LC50 Inhalation - Rat	> 1.9 mg/l air Animal: rat, Guideline: EPA OPP 81-3 (Acute inhalation toxicity)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID

Acetic acid, methyl ester (79-20-9)	
LD50 oral rat	6482 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 oral	6482 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal	5000 mg/kg
ATE CA (oral)	6482 mg/kg bodyweight
ATE CA (Dermal)	5000 mg/kg bodyweight

2-Methylpentane (107-83-5)	
LD50 oral rat	≈ 15.84 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat (Vapours)	> 20 mg/l

Pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	2500 mg/kg
LD50 dermal	3000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l air (4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	364 mg/l Source: ChemIDplus

Hexane (110-54-3)	
LD50 oral rat	16000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 oral	15800 mg/kg
LD50 dermal rabbit	> 3350 mg/kg bodyweight (Equivalent or similar to OECD 402, 4 h, Rabbit, Male, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 17.6 mg/l air (Equivalent or similar to OECD 403, 24 h, Rat, Male, Experimental value, Inhalation (vapours), 30 day(s))
LC50 Inhalation - Rat (Vapours)	259.354 mg/l Source: ECHA

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: other:

Skin corrosion/irritation : Causes skin irritation.

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
pH	8

Acetic acid, methyl ester (79-20-9)	
pH	No data available in the literature

2-Methylpentane (107-83-5)	
pH	No data available in the literature

Pentane (109-66-0)	
pH	No data available in the literature

Hexane (110-54-3)	
pH	7 (< 0.01 %, 25 °C)

Serious eye damage/irritation : Causes serious eye irritation.

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
pH	8

Acetic acid, methyl ester (79-20-9)	
pH	No data available in the literature

2-Methylpentane (107-83-5)	
pH	No data available in the literature

Pentane (109-66-0)	
pH	No data available in the literature

Hexane (110-54-3)	
pH	7 (< 0.01 %, 25 °C)

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Acetic acid, methyl ester (79-20-9)	
LOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:

Pentane (109-66-0)	
NOAEL (animal/male, F0/P)	300 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
NOAEL (animal/female, F0/P)	≥ 1000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]

STOT-single exposure : May cause drowsiness or dizziness.

Acetic acid, methyl ester (79-20-9)	
STOT-single exposure	May cause drowsiness or dizziness.

2-Methylpentane (107-83-5)	
STOT-single exposure	May cause drowsiness or dizziness.

Pentane (109-66-0)	
STOT-single exposure	May cause drowsiness or dizziness.

Hexane (110-54-3)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
NOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Acetic acid, methyl ester (79-20-9)	
NOAEC (inhalation, rat, 28 days)	6.66 mg/l
NOAEC (inhalation, rat, 90 days)	1.06 mg/l

Pentane (109-66-0)	
NOAEC (inhalation, rat, vapour, 90 days)	30 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: other:, Guideline: EPA OTS 798.2450 (90-Day Inhalation Toxicity), Guideline: other:, Guideline: other:

Hexane (110-54-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

RED “N” TACKY® Spray Grease	
Vaporizer	Aerosol
Viscosity, kinematic	< 20.5 mm²/s @ 40 ° C

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	18 mm²/s
Hydrocarbon	Yes
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Acetic acid, methyl ester (79-20-9)	
Viscosity, kinematic	No data available in the literature

2-Methylpentane (107-83-5)	
Viscosity, kinematic	0.47 mm²/s (20 °C, Calculated)

Pentane (109-66-0)	
Viscosity, kinematic	0.2 – 0.52 mm²/s (20 °C, ASTM D7042: Dynamic viscosity and density of liquids)

Hexane (110-54-3)	
Viscosity, kinematic	No data available in the literature

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : May cause eye irritation. Eye irritation.
Symptoms/effects after ingestion : May cause irritation to the digestive tract. Risk of lung oedema.

SECTION 12 Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short–term (acute) : Not classified.
Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
LC50 - Fish [1]	10000 mg/l Source: ECHA
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
LC50 - Fish [1]	> 0.0013 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

Acetic acid, methyl ester (79-20-9)	
LC50 - Fish [1]	250 – 350 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	1027 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	> 120 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	> 120 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

2-Methylpentane (107-83-5)	
LC50 - Fish [1]	1.478 mg/l (96 h, Pimephales promelas, QSAR)
EC50 96h - Algae [1]	4.321 mg/l (US EPA, Algae, Calculated value)

Pentane (109-66-0)	
LC50 - Fish [1]	4.3 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	2.7 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value)
ErC50 algae	11 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Selenastrum capricornutum, Static system, Fresh water, Experimental value, GLP)
NOEC chronic algae	2 mg/l

Hexane (110-54-3)	
LC50 - Fish [1]	2.5 mg/l
EC50 - Crustacea [1]	3.9 mg/l

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)	
EC50 - Crustacea [1]	3 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	20 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

RED “N” TACKY® Spray Grease	
Persistence and degradability	Not rapidly degradable

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
Persistence and degradability	Not rapidly degradable

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
Persistence and degradability	Not rapidly degradable

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Persistence and degradability	Not rapidly degradable

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable

Acetic acid, methyl ester (79-20-9)	
Persistence and degradability	Readily biodegradable in water.

2-Methylpentane (107-83-5)	
Persistence and degradability	Readily biodegradable in water.

Pentane (109-66-0)	
Persistence and degradability	Readily biodegradable in water.

Hexane (110-54-3)	
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.
ThOD	3.52 g O_2/g substance

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)	
Partition coefficient n-octanol/water (Log Pow)	> 4.46 Source: ECHA

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID

Acetic acid, methyl ester (79-20-9)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)

2-Methylpentane (107-83-5)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF - Fish [1]	356 (Pisces, Literature study, QSAR)
Partition coefficient n-octanol/water (Log Pow)	3.214 (Calculated, KOWWIN, 25 °C)

Pentane (109-66-0)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Partition coefficient n-octanol/water (Log Pow)	3.5 (Experimental value, 25 °C)

Hexane (110-54-3)	
Bioaccumulative potential	Not bioaccumulative.
Partition coefficient n-octanol/water (Log Pow)	4 (Experimental value, Equivalent or similar to OECD 107, 20 °C)

12.4. Mobility in soil

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)	
Mobility in soil	35900000 Source: EPISUITE

Acetic acid, methyl ester (79-20-9)	
Surface tension	24 mN/m (20 °C)
Ecology - soil	Highly mobile in soil.

Acetic acid, methyl ester (79-20-9)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

2-Methylpentane (107-83-5)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for adsorption in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.044 – 2.786 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

Pentane (109-66-0)	
Surface tension	15.49 mN/m (25 °C, 100 %)
Ecology - soil	Low potential for adsorption in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.9 (log Koc, QSAR)

Hexane (110-54-3)	
Surface tension	17.89 mN/m (25 °C, 1 g/l)
Ecology - soil	Low potential for mobility in soil.
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.34 (log Koc, QSAR)

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)	
Mobility in soil	518.5 Source: EPISUITE

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector’s sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.
Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with TDG / DOT / IMDG / IATA

TDG	DOT	IMDG	IATA
14.1. UN Number			
UN1950	UN1950	UN1950	UN1950

TDG	DOT	IMDG	IATA
14.2. UN Proper Shipping Name			
AEROSOLS	Aerosols	AEROSOLS	Aerosols, flammable
Transport document description			
UN1950 AEROSOLS, 2.1	UN1950 Aerosols, 2.1	UN UN1950 AEROSOLS, 2.1	UN UN1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group, if applicable			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

TDG

UN-No. (TDG) : UN1950

TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment),107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L

Excepted quantities (TDG) : E0

Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L

Emergency Response Guide (ERG) Number : 126

DOT

UN-No. (DOT) : UN1950

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Special provisions (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	:	SP277
Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P207, LP200
Special packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	:	S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

IATA

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provisions (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78[9] and the IBC Code[10]

Not applicable

SECTION 15 Regulatory information

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)

Listed on the Canadian DSL (Domestic Substances List)

Sulfonic acids, petroleum, calcium salts (61789-86-4)

Listed on the Canadian DSL (Domestic Substances List)

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Acetic acid, methyl ester (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

2-Methylpentane (107-83-5)

Listed on the Canadian DSL (Domestic Substances List)

Pentane (109-66-0)

Listed on the Canadian DSL (Domestic Substances List)

Hexane (110-54-3)

Listed on the Canadian DSL (Domestic Substances List)

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)

Listed on the Canadian DSL (Domestic Substances List)

RED “N” TACKY® Spray Grease

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts (68584-23-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Sulfonic acids, petroleum, calcium salts (61789-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Benzenamine, ar-nonyl-N-(nonylphenyl)- (36878-20-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Acetic acid, methyl ester (79-20-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

2-Methylpentane (107-83-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Pentane (109-66-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Hexane (110-54-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

1,3,4-Thiadiazole-2(3H)-thione, 5,5'-dithiobis- (72676-55-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16 Other Information

Issue date	:	03/04/2025
Revision date	:	07/16/2026
Supersedes	:	07/07/2026

Full text of hazard classes and H-statements:	
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurized container; may burst if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.